

## LINK SERIES - LED Integrated Linear Tube Kit

The LINK SERIES - LED Integrated Linear Tube Kit, 4-FT or 8-FT w/ Easy Links, 140 lm/W, IP22 Dry Location, Type B, Premium Surface Mount Daisy Chain Lamp.

Project:
Date:
Catalog No:
Prepared By:

### Premium Features

Lumen Output	4200 to 8400 lumens
Efficacy	140 lm/W
Input Voltage	120-277V
Driver	Type B (Internal Driver)
Installation	Surface Mount and Daisy Chain
Dimmable	No
CCT	5000K
IP Rating	IP22 Dry Location
Size	4-FT or 8-FT each
Warranty	5 Years

### Applications

Premium indoor daisy chain lamp kit. Suitable for mounting on shop light fixtures and flat surfaces.

### Construction

Manufactured for durability and heat dissipation using aluminum sheet backing. IP22 Dry Location rated for protection against solid objects 12.55mm diameter and greater, vertically falling water drops with enclosure tilted: IEC 60529.

### Electrical

Input voltages 120-277V. Type-B, to operate without a ballast. Tombstone free, standalone installations. 4-FT Kits (Link up to 20 4-FT Tubes at 220-277V, or up to 10 4-FT Tubes at 120V). 8-FT Kits (Link up to 10 8-FT Tubes at 220-277V, or up to 5 8-FT Tubes at 120V). Operating temperatures -22°F to 149°F (-30°C to 65°C).

### Mounting

Includes Surface Mount Metal Clips with Screws per tube, Long and Short Easy Link Connectors to Daisy Chain, Connector End Cap, and Input Connector.

### Optics

V-Curved 180° Beam Angle, Anti-UV Clear or Frosted Polycarbonate Lens available.

### Controls

Compatible with ON/OFF occupancy sensors.

### Listings

ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. Listed to qualify for energy-efficient LED lighting rebates.

### Warranty

5 yr /50K hrs. View at: <https://falkorindustry.com/warranty/>.

Linkable 4-FT and 8-FT Models



\*Shown with Long Easy Link Connector



\*Shown with Short Easy Link Connector

### Correlated Color Temperature (CCT)

5000K



## Specifications

### Energy Data

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: 30W, 60W

Power Factor: >0.95

Total Harmonic Distortion (THD): <20%

Operating Temperature: -22°F to 149°F (-30°C to 65°C)

### Lighting Data

Lumens: 4200, 8400

Lumens Per Watt: 140 lm/W

Color Correlated Temperature (CCT): 5000K

Dimmable: No

Color Rendering Index (CRI): >80

L70: 50000 hours

## Ordering Information

Model	Size	Lens	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Dimensions	Weight
ZS-T8-30P4FT-INT(5000K)-Frosted	4-FT	Frosted	30W	120-277V	0.25A@120V, 0.11A@277V	4200	140 lm/W	5000K	No	47.44"L x 1.30"W x 1.38"H	0.66 lbs
ZS-T8-30P4FT-INT(5000K)-Clear	4-FT	Clear	30W	120-277V	0.25A@120V, 0.11A@277V	4200	140 lm/W	5000K	No	47.44"L x 1.30"W x 1.38"H	0.66 lbs
ZS-T8-60P8FT-INT(5000K)-Frosted	8-FT	Frosted	60W	120-277V	0.50A@120V, 0.22A@277V	8400	140 lm/W	5000K	No	93.50"L x 1.30"W x 1.38"H	1.43 lbs
ZS-T8-60P8FT-INT(5000K)-Clear	8-FT	Clear	60W	120-277V	0.50A@120V, 0.22A@277V	8400	140 lm/W	5000K	No	93.50"L x 1.30"W x 1.38"H	1.43 lbs

## Shipping Information

Model Size	Unit Weight	Shipping Dimensions	Shipping Weight	Quantity /Box
4-FT	0.66 lbs	49.60"L x 16.93"W x 9.84"D	42.33 lbs	50
8-FT	1.43 lbs	96.06"L x 8.66"W x 8.27"D	33.07 lbs	20

## Physical Dimensions

**4-FT Models**      47.44"L x 1.30"W x 1.38"H

**8-FT Models**      93.50"L x 1.30"W x 1.38"H

