

FL0224D-PD FL0239D-PD FL0254D-PD



Linear Pendant

Features

Housing

Die-formed Cold-rolled Steel and Aluminum Extrusion
 Finish Option: -62 Satin Nickel -01 Polish Brass -06 White -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.

Electrical

High Power Factor, Low THD

Lamp


LED Type: Built-in (Color Temperature Option – 3500K, 5000K)

Certification

ETL/cETL Listed for Damp Locations, Energy Star

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT / CRI	Lumen (TYP)	Dimension (L X W X H1/H2)	Finish	Energy Star
FL0224D-PD-3000K	120V ~ 277V	11W	3000K / 80	935	22.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes
FL0224D-PD-4000K	120V ~ 277V	11W	4000K / 80	980	22.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes
FL0239D-PD-3000K	120V ~ 277V	18W	3000K / 80	1530	34.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes
FL0239D-PD-4000K	120V ~ 277V	18W	4000K / 80	1600	34.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes
FL0254D-PD-3000K	120V ~ 277V	23W	3000K / 80	1950	46.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes
FL0254D-PD-4000K	120V ~ 277V	23W	4000K / 80	2050	46.0" x 4.8" x 2.7"/5'	Satin Nickel	Yes