


# LED Generic Ceiling Cloud

## DIMENSIONS



GCC-11 (11" Pan)  
A. Diameter = 11"  
B. Height = 3-1/2"

GCC-14 (14" Pan)  
A. Diameter = 14"  
B. Height = 3-1/2"

GCC-19 (19" Pan)  
A. Diameter = 19"  
B. Height = 4



## APPLICATION

The LED Based GCC series is a ceiling or wall mount series which can be used in a broad range of residential and commercial applications. This series provides customers with a high quality luminaire utilizing the latest LED, solid state lighting and electronic driver technology for optimal performance and maximized energy efficiency. With a traditional opal white lens, the GCC series produces even and uniform light distribution and ideal choice for offices, corridors, stairways, bedroom, closet, and foyers applications where customers are replacing incandescent, circline or compact fluorescent lamps.

## FEATURES

- High-transmission (White) Acrylic lens with excellent distribution and uniformity.
- Full distribution LED Luminaire
- Designed for a 50,000 Hour Life
- Available in 3000K or 4000K Kelvin temperatures
- Environmentally friendly - contains no mercury or other hazardous materials
- Diffuser is .080" thick vacuum formed smooth white acrylic

## QUICK SHIP

GCC-11-13-120D-940  
GCC-14-17-120D-940  
GCC-14-26-MV-940  
GCC-19-34-MV-940

## HOUSING

Features a white acrylic and white powder coated steel pan. Available in 11" and 14" diameters.

## MOUNTING

Designed for mounting on 4" electrical.

## ELECTRICAL

Equipped standard with 120V 15-100% triac dimming driver.

## LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

## WARRANTY

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

## ORDERING INFORMATION

Example Model Number: GCC-11-13-120D-840-MOS

GCC	SIZE	WATTAGE	DRIVER TYPE	COLOR TEMPERATURE	OPTIONS
11- 11" Pan <sup>2</sup> 14- 14" Pan <sup>2</sup> 19- 19" Pan <sup>2</sup>	11" Pan 13- 13W, 1000 Lumens <sup>2</sup> 14" Pan 17- 17W, 1700 Lumens <sup>2</sup> 26- 26W, 2600 Lumens <sup>2</sup> 19" Pan 34- 34W, 3400 Lumens <sup>2</sup>	120D- 120V, Triac Dimming <sup>2</sup> MV- 120-277V	840- 80 CRI; 4000 Kelvin <sup>1</sup> 930- 90 CRI; 3000 Kelvin <sup>1</sup> 940- 90 CRI; 4000 Kelvin <sup>2</sup>	MOS- Integral Microwave Sensor EML8- Emergency Battery Pack, 800 Lumens EML14- Emergency Battery Pack, 1400 Lumens	

Notes:

<sup>1</sup>Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.

<sup>2</sup>Energy star listed