Lampholders

12/15/2009

HID Lampholders

Wh Cop	mpholder – Enclosed-fixture Medium Base	
Lan • •	hite glazed porcelain body with wireways. Copper alloy, nickel-plated screw shell. pper alloy, nickel-plated center contact. Two leads are No. 18 AWG 200° 600V glass aid SEW-2, black and white, 9" long, stripped ½". Two #6-32 captive mounting nuts. mpholder is cULus listed. 660W 600VAC 4KV Pulse Rated	
Wh Iam cen whi •	 ampholder – Enclosed-fixture Mogul Base hite glazed porcelain body with wireways. Copper alloy, nickel-plated screw shell with np grips. Stainless steel coil spring under center contact. Copper alloy, nickel-plated neer contact. Two leads are No. 14 AWG 200° 600V glass braid SEW-2, black and ite, 12" long, stripped ½". Two #8-32 mounting nuts. Lamp holder is cULus listed. 1,500W 600VAC 5KV Pulse Rated 	
Ligh con lead strip •	ampholder – Open-fixture Mogul Base ht pink glazed porcelain body with wireways. Copper alloy, nickel-plated center ntact and lamp-grip screw shell. Stainless steel coil spring under center contact. Two ids are No.14 AWG 200° 600V glass braid SEW-2, black and white, 11" long, ipped ½". Two #8-32 captive mounting nuts. Lampholder is cULus listed. 1,500W 600VAC 5KV Pulse Rated	

c(UL)us

Specifications are subject to change without notice.



Lighting for life.

Visit us online at HowardLightingProducts.com or call us at 800.956.3456.