



**PRISM** MR11 & MR16 GU10



**Technical Data**

- GU10 base
- 20, 35 and 50 watts
- 120 volt
- Aluminized reflector does not deteriorate, ensuring consistent color throughout lamp life
- Protective glass lens
- Integrated UV protection
- High lumen maintenance, greater than 90% throughout lamp life

**Benefits**

- No color shift
- Greatly reduces fading by UV exposure
- Safe for operation in open fixtures

- » No color shift
- » Protective glass lens
- » UV protection

**Markets:**

- Residential
- Commercial

**Applications:**

- Display lighting
- Accent lighting
- General lighting
- Decorative lighting

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at [halcolighting.com](http://halcolighting.com)



# MR11 & MR16 GU10

Catalog Number: \_\_\_\_\_ Type: \_\_\_\_\_

Project: \_\_\_\_\_

Comments: \_\_\_\_\_ Date: \_\_\_\_\_

Prepared By: \_\_\_\_\_

HALOGEN

## Ordering Information

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CBCP	Filament Design	Avg. Life	Pkg. Qty.	Beam Spread	MOL
<b>MR11</b>												
20 Watt	GU10	107544	MR11FL20/L/GU10	Flood w/Lens	120V	3000	220	CC-2V	2000	10/200	30°	1.38"
35 Watt	GU10	107546	MR11FL35/L/GU10	Flood w/Lens	120V	2850	560	CC-2V	2000	10/100	30°	1.38"
<b>MR16</b>												
20 Watt	GU10	107152	MR16FL20/L/GU10	Flood w/Lens	120V	2800	170	CC-2V	2000	10/200	30°	2.16"
35 Watt	GU10	107154	MR16FL35/L/GU10	Flood w/Lens	120V	2800	900	CC-2V	2000	10/100	30°	2.16"
50 Watt	GU10	107180	MR16FL50/L/GU10	Flood w/Lens	120V	2900	1500	CC-2V	2000	10/100	30°	2.16"