

LED Bypass/Line Voltage T8 Tube Lights : High Lumen



- 20 watts
- 2,950 lumens
- 148 lpw
- universal burn

Features

- Solid state replacement for T12 G13 base linear fluorescent
- Single-end powered, operates on 120V-277V line voltage
- Frosted lens for uniform diffuse appearance
- No external ballast or driver required
- Ultra-high performance LEDs deliver 148 lpw
- Up to 50% instant energy savings
- 4000K or 5000K CCT
- Instant-On with no warm up like fluorescents
- Contains no lead or mercury, RoHS Compliant
- Existing fixture maintains original UL compliance per UL1598C listing
- Suitable for use in totally enclosed fixtures



Performance

- 80+ CRI
- Integral 120~277V drivers provide easy installation
- Wide ambient temperature range from -20°C (-4°F) to 40°C (104°F)
- <20% Total Harmonic Distortion
- For use with non-shunted tombstone lampholders
- UL 1598C listed
- Contains no mercury or lead; classified as non-hazardous waste

Applications

- Commercial
- Industrial
- Hospitality
- Education
- Healthcare
- Retail

Ordering Information

Order Code	Item #	Lngh	W	Lm	CCT	CRI	Bm	Appearance	Envelope	Life/Hrs
<b>09897</b>	T8-PF-05C-40K-U	4'	20W	2,950	4000K	80+	140°	Frosted	Polycarb	50K
<b>09418</b>	T8-PF-05C-50K-U	4'	20W	2,950	5000K	80+	140°	Frosted	Polycarb	50K

NOTE: Use order code when ordering.



Rev. 11/20/17

selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975  
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335