

## **7W LED High CRI PAR20 Flood Dimmable - 5000K**

## Item # 700

L7HPAR20DIM/FL/50K

1	1 LAMP SPECIFICATION						
1-1	Lamp Type		LED 90CRI PAR20				
1-2	Dimmable (Y/N)		YES				
1-3	Base		E26				
1-4	Lamp Finish/Type		PAR20				
1-5	amp Wattage		7W				
1-6	Wattage Comparison (FC on Floor)		50W Incand (based on Floor Lux)				
1-7	Rated Average Life (hours) L70		25,000		V-111		
1-9	Reliable Operating Temperature	-4F to 113F					
2	Photometric Characteristics						
2-1	Initial Lumens		450				
2-2	Centre Beam Candle Power (Cd)		800				
2-3	Beam Angle (50% I Max) in Degree		40			7	
2-4	Beam Angle (10% I Max) in Degree		N/A				
2-5	Initial Lumens per Watt		64				
2-6	Color Temperature		5000K C(UL)us ROLLS				
2.7	Color Rendering Index (CRI)		90				
3	Electrical Characteristics						
3-1	Input Line Voltage/Frequency		120V 60 Hz	3-2	Power Factor	0.96	
3-3	Lamp rated Wattage		7W	3-4	Input Line Current	65mA	
3-5	Total Harmonic Distortion		22%	3-6	Dimming Range in %	Full	
4	Dimensional Characteristics						
4-1	Nominal Length (Inches/mm)		3.23"/82mm	4-2	Diameter	2.48"/63mm	
5	Product Information						
5-1	Description	7W LED 90CRI PAR20 Dimmable FLOOD - 5000K					
5-2	Primary Application	Household Use, Office & Commercial- Wet Location					
5-3	Warranty	5 Years from c	late of purchase				
5-4	TCLP Compliant YES			5-6	RoHS Compliant	YES	
5-5	Energy Star or LM79 (Y/N) NO			5-8	UL / FCC	YES	
6	PACKING DETAILS						
6-1	Color Box Size (Inches) 1x1	2.48 x 2.48 x 3.54	4	6-2	Inner Carton Size (Inches)	N/A	
6-3	Master Carton Size (Inches) 1x12	10.83 x 8.19 x 4.3	80	6-4	Gross Weight / Net Weight ( lbs )	2.16 / 1.45	
05/20	05/2019© Overdrive For more information visit www.overdrive-lighting.com						

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.