


LED Ringed Light Vanity

DIMENSIONS



APPLICATION

The RVL Series tiered contemporary framed wall mounted vanity fixture and is available in two finish options, satin nickel or oil rubbed bronze. Updated with the latest in LED technology The RVL is an elegant lighting solution that can be used in various applications including corridors and restrooms. Fixture mounts to standard junction box (not included). The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects.

FEATURES

- High-transmission (White) Acrylic lens with excellent distribution and uniformity
- Direct replacement for fluorescent
- NEC Required disconnect is standard
- Full distribution LED Luminaire
- Direct replacement of fluorescent
- 3000 Kelvin

HOUSING

Contemporary slyed fixture. Twin steel rings surround a milk white acrylic diffuse provides widespread and even illumination.

MOUNTING

Designed for mounting on 4" electrical.

ELECTRICAL

Equipped standard with 120V 15-100% triac dimming driver.

LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

WARRANTY

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

QUICK SHIP

RVL-24-17-MV-930-NS

ORDERING INFORMATION

Example Model Number: RVL-24-26-MV-930-NS

RVL					
SERIES	LENGTH	WATTAGE	DRIVER TYPE	COLOR TEMPERATURE	FINISH
	24- 24" Length ² 36- 36" Length ¹ 48- 48" Length ¹	24" Housing 17- 17W, 2000 Lumens 26- 26W, 2700 Lumens ¹ 36" Housing 26- 26W, 2700 Lumens ¹ 48" Housing 34- 34W, 3400 Lumens ¹	120D- 120V, Triac Dimming ^{1 2} MV- 120-277V	930-90 CRI; 3000 Kelvin ¹ 940-90 CRI; 4000 Kelvin	NS- Nickel Satin ² ORB- Oil Rubbed Bronze ^{1 2}

Notes:

¹Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.

²Energy star listed