

LFX/EC/3'/25W/MV/D/DLC/50K ACRY DIFF FIXTURE SUN

Item: 85356-SU



Fixture Life Hours 50000 Hours Bulb Integrated LED Finish White

133.36 Lumens Per Watt (LPW) Life (based on 3hr/day) 45.7

Estimated Energy Cost \$3.01 per Year

Safety Rating UL Listed - Damp Location

Dimmable True DLC True

Fixture Characteristics

Collection Strip Fixture Style Modern Shape Linear **Number of Lights** 1 - Light Mounting Surface Use Location Indoor

Electrical Characteristics

Watts 25 120-277 Volts LED Chip Manufacturer **SEOUL** Number of LEDs 3528

Operating Temperature -20° to 50° C

Light Characteristics

Brightness 3334 Lumens

Color Accuracy (CRI) 80

Super White Light Appearance **Color Temperature** 5000K

Product Dimensions

Size

Item Dimensions (in) (W) 3.35 (H) 3.56 (D) 36.00 Package Dimensions (in) (W) 3.75 (H) 3.75 (D) 38.00

Product Data

Item Number 85356-SU

Case Quantity

Barcode on SKU 653703853567 Barcode on Case 10653703853564

Brand SUNLITE

LFX/EC/3'/25W/MV/D/DLC/50K Description

DLC File Number PVS830YH



Sunlite 85356 3 ft. LED Garage Linear Wraparound Strip Lighting Fixture, Ceiling Flush Mount, 25 Watt, 5000 - Super White

- This 3 Foot LED linear strip fixture is both esthetically pleasing and functional. These fixtures will enhance any space and can be used in workshops, offices, factories, showcases or utility areas.
- White aluminum body with frosted lens diffuser. Fixture body has multiple knockouts for convenient installation. This LED lighting fixture does not contain any mercury or
- This fixture will produce 50,000 hours of light without maintenance. It draws 25 watt of electricity and therefore more energy efficient, and are a replacement for, 3ft 25 watt fluorescent fixtures.
- This fixture has a UL safety rating and is rated to be used in damp locations. The fixture has a 5 year warranty. This lighting fixture can dim to 10%.
- This fixture can be mounted flat on a ceiling or can be suspended. Fixture includes junction box mounting hardware.





