



Sunlite LFX/PTL/80W/50K 80 Watt Integrated LED Lamp Super White

The Sunlite outdoor area pole-top fixtures are ideal for parking areas, airports and amusement parks. Their high output LEDs ensure the area is well lit while conserving energy. The circular light is directed downward providing a pleasant illumination over the designated area. These fixtures mount on a three inch post.



General Characteristics

Fixture Life Hours	50000 Hours
Bulb	Integrated LED
Finish	Bronze
Lumens Per Watt (LPW)	110.20
Life (based on 3hr/day)	45.7
Estimated Energy Cost	\$9.64 per Year
Safety Rating	ETL Listed - Wet Location
DLC	True

Fixture Characteristics

Collection	Circular Pole-Top
Number of Lights	1 - Light
Mounting	Pole
Use Location	Outdoor

Electrical Characteristics

Watts	80
Volts	120-277
Equivalent Watts	175-320
LED Chip Manufacturer	Philips 3030
Number of LEDs	90
Power Factor	0.92
Operating Temperature	-40° to 40° C

Light Characteristics

Brightness	8816 Lumens
Color Accuracy (CRI)	70
Light Appearance	Super White
Color Temperature	5000K
Beam Angle	105°-105°

Product Dimensions

Height (in)	25
Diameter (in)	18
Package Dimensions (in)	(W) 19.60 (H) 7.63 (D) 19.60

Product Data

Item Number	49181-SU
Case Quantity	1
Barcode on SKU	653703491813
Brand	SUNLITE
Description	LFX/PTL/80W/50K
DLC File Number	PFOQF300