

LFX/STL/300W/MV/50K LED STREET LIGHT SUNLITE



Sunlite LFX/STL/300W/MV/50K 300 Watt Integrated LED Lamp Super White

The Sunlite high output street lights are ideal for lighting large areas. They are typically found on walkways, ramps, roadways and bike paths. Their high luminous efficiency provides high visibility while using significantly less energy. These fixtures can be mounted onto a pole, junction box or trunnion mounting (sold separately). The photo cell sensor option (sold separately) can save money and energy by automatically turning off the light when daylight is detected.



General Characteristics

Fixture Life Hours	50000 Hours
Bulb	Integrated LED
Lumens Per Watt (LPW)	116.88
Life (based on 3hr/day)	45.7
Estimated Energy Cost	\$36.13 per Year
Safety Rating	ETL Listed - Wet Location
DLC	True

Fixture Characteristics

Collection	High Output Street Light
Shape	Strip
Number of Lights	1 - Light
Mounting	Pole
Use Location	Outdoor

Electrical Characteristics

Watts	300
Volts	120-277
Equivalent Watts	1000-1500
LED Chip Manufacturer	Philips 3030
Number of LEDs	360
Power Factor	0.92
Operating Temperature	-40° to 40° C

Light Characteristics

Brightness	35064 Lumens
Color Accuracy (CRI)	70
Light Appearance	Super White
Color Temperature	5000K
Beam Angle	100°-60°

Product Dimensions

Item Dimensions (in)	(W) 14.25 (H) 3.74 (D) 23.56
Package Dimensions (in)	(W) 24.00 (H) 5.74 (D) 15.66

Product Data

Item Number	85325-SU
Case Quantity	1
Barcode on SKU	653703853253
Brand	SUNLITE
Description	LFX/STL/300W/MV/50K
DLC File Number	PI8MI1EN