

# Sunlite 85321-SU LED Outdoor Street Light, 50K - Super White, 3420 Lumen, 30 Watt, Bronze Finish

# **DESCRIPTION:**

Sunlite LED Street Light fixtures provide ample outdoor illumination and high visibility. With a bright 3420 lumen output at 5000K Super White color temperature they are an energy efficient solution for your lighting needs. Each fixture uses only 30 watts with a low estimated yearly energy cost of \$3.61. (Based on 3 hours/day use at \$0.11/kWh) Ideal for commercial, industrial, roadway, parking lot and pathway lighting. Long life, LED technology built-in means no bulbs to replace and up to 50,000 hours of maintenance-free service. ETL Listed for wet location installation and DLC Listed for quality and efficiency.

# FEATURES:

- LED TECHNOLOGY Sunlite LED Street Light Fixtures provide ample illumination and high visibility while saving energy. Each fixture contains 36 high output LEDs.
- ENERGY EFFICIENT Using only 30 watts of energy these fixtures have a low estimated yearly energy cost of \$3.61. (Based on 3 hours/day use at \$0.11/kWh) With a 50,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- HIGH LUMEN OUTPUT Each fixture contains 36 high output LEDs and gives off a bright 3420 lumen output with 5000K super white color temperature.
- MULTIPLE OUTDOOR USES These commercial grade fixtures are made from weather resistant die-cast aluminum with a bronze finish. Ideal for commercial, industrial, roadway, parking lot and pathway lighting. Mounting hardware sold separately.
- ETL AND DLC LISTED These fixtures are ETL Listed for wet location installation and DLC Listed for quality and efficiency. They operate on 120-277 volt service.





# SPECIFICATIONS:

### **General Characteristics**

Bulb Shape Average Rated Hours Finish Average Life Span Years Dimmable

Dimmable
Material
Lens Finish
Bulb Type

### **Electrical Characteristics**

Watts 30
Volts 120-277
Equivalent Wattage 70-100
LED Chip Manufacturer Philips 3030
Power Factor 0.92

Integrated LED

50000

**Bronze** 

46

No

Metal

Clear

Integrated

-40° to 40° C

3420

Temperature

# **Light Characteristics**

Lumens Brightness Color Rendering Index CRI

Color Rendering Index CRI

Emitted Color

Color Temperature Kelvin

Beam Angle

Mercury Content

5000K

100°-60°

5

### Fixture Characteristics

Number of Lights1MountingOtherFixture TechnologyLEDUse LocationOutdoor

# **Additional Features**

Safety Rating Mark
Safety Rated For Canada
Safety Rated For USA
DLC
PLC Standard

ETL Listed - Wet Location
Yes
Yes
Standard

### **Product Dimensions**

Item Dimension (in)
Item Weight (lb)
Package Dimension (in)
Package Weight (lb)

### **Product Data**

Case Unit Rate Item UPC Warranty Years (W) 4.54 (H) 2 (D) 7

2.030

(W) 2.9 (H) 8.8 (D) 9.1

2.100

10

653703853215

5

