

# **10.5W LED 90CRI PAR30** Dimmable FLOOD - 3000K

# Item # 631

L10HPAR30DIM/FL/30K

#### LAMP SPECIFICATION

1-1 Lamp Type LED 90CRI PAR30

1-2 Dimmable (Y/N) YES

1-3 Base E26

PAR<sub>30</sub> 1-4 Lamp Finish/Type

1-5 Lamp Wattage 10.5W

1-6 Wattage Comparison (FC on Floor) 75W Incand (based on Floor Lux)

1-7 Rated Average Life (hours) L70 25,000

1-8 Reliable Operating Temperature -4F to 113F

# **Photometric Characteristics**

2-1 Initial Lumens 720

2-2 Centre Beam Candle Power (Cd) 1440

2-3 Beam Angle (50% I Max) in Degree 40(Flood)

2-4 Beam Angle (10% I Max) in Degree N/A

2-5 Initial Lumens per Watt 69

2-6 Color Temperature 3000K

2.7 Color Rendering Index (CRI) 90

#### **Electrical Characteristics**

3-1	Input Line Voltage/Frequency	120V 60 Hz	3-2	Power Factor	0.96
3-3	Lamp rated Wattage	10.5W	3-4	Input Line Current	90 mA
3-5	Total Harmonic Distortion	18%	3-6	Dimming Range in %	Full

#### **Dimensional Characteristics**

4-1 Nominal Length (Inches/mm) 3.62"/92mm 3.74"/95mm Diameter 4-2

### **Product Information**

5-1 Description	10.5W LED 90CKI PAK30 DIMMable FLOOD - 3000K
5-2 Primary Application	Household Use, Office & Commercial - Wet location

5 Years from date of purchase 5-3 Warranty

5-4 TCLP Compliant YES 5-6 RoHS Compliant YES 5-8 UL/FCC YES

5-5 Energy Star or LM79 (Y/N) ES

# **PACKING DETAILS**

6-1 Color Box Size (Inches) 1x1 3.9 x 3.9 x 4.0 Inner Carton Size (Inches) 1x12 N/A

6-3 Master Carton Size (Inches) 1x12 16.65 x 12.60 x 6.22 6-4 Gross Weight / Net Weight (lbs) 7.07 / 4.76

01/2017© Overdrive For more information visit www.overdrive-lighting.com

Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.







