



Recessed Ceiling

33 W

200 W

110°

80

Max 5 No 12 AWG or 8 No 14 AWG

0.98

Insulated Ceiling, Wet & Damp Locations

IP 54

Yes

-40°F (-40°C) to +104°F (+40°C)

70% Light Output at 50,000 Hours

cULus, Energy Star

10 Year Residential / 5 Year Commercial

Black

4100

2400

Triac Dimmable

0-10V Dimmable



Location:	
Cat #: Qty:	

SPECIFICATION

3000

2200

120V AC

AVAILABLE TRIMS

Sold Separately

Low Volage Extension Cables 6ft - cat # EXC6, 20ft - cat # EXC20 Max 40 ft Allowed, FT4 / CMR rated

Flat Rough-In Plates - cat # RIP8

Goof Ring White OD 9 1/2" cat # GR8

Goof Ring White OD 10 1/2" cat # GR810

120V-347V AC

Type IC, Wet & Air-Tight

DESCRIPTION

8" Round Recessed LED With Integral Driver In Connection Box


## **FEATURES & BENEFITS**

1 3/4" Deep - Install Where Ceiling Space Is Limited Driver Inside Connection Box - No Junction Box Needed Fast & Easy To Install - Save On Labor Type IC Rated - No Housing Required

### MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 1 3/4"

DIMENSIONS: ID 7 1/4" OD 9" Cut Out 7 1/2" to 8"



# 120V TRIAC Dimmable Driver Included



41K

Optional 120V - 347V Driver 0-10V Dimmable



4100K

Order Separately as Cat # LLL-LD3580T

Black

ORDERING GUIDE Example: LY82RCD / 30K / WH					
	CC	T Trim Finish	_		
LY82RCD	1	1			
3000K	30	к wh	White		

BK

www.LotusLEDLights.com

Notes:

Applications

Energy Used

Colour Temperature

Light Output

Halogen Equivalent

Beam Angle

CRI

Default Driver Input

**Optional Driver Input** 

Junction Box Wire Capacity

Power Factor

Approved Location

**IP** Rating

Air Tight

Ambient Temperature

**Projected Life** 

Certification

Warranty

ACCESSORIES

White

# Lotus LED Lights CANADA

Type IC

Air-Tight

Lotus LED Lights USA 250 H Street # 301, Blaine WA 98230 tel 360-200-5500 Hainesport NJ, Naples FL, Dallas TX, Vancouver WA

COMPLIANCE

US LISTED

800-15355 24 Ave Box 200, Surrey BC	V4A 2H9 tel 604-538-3090
	Delta BC & Mississauga ON