

## LED 8FT 36W Internal Tube

### FEATURES

- Easy to install 2 pieces combined into 1
- Low thermal decay & maintenance
- Bracket included to prevent rotating and bending
- No Mercury, UV or Lead
- 50,000 hours lifetime

### SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports



### CONSTRUCTION:

Aluminum + PC housing. Frosted lens.

### ELECTRICAL:

Available as 120-277V input. -20°C to 50°C, -4°F to 122°F

### OPTICAL SYSTEM:

120° beam angle.

### INSTALLATION & MOUNTING:

Double ended Type B. FA8 base

### WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.



MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	REPLACES
LOD-36WT88FTF-40KB	36W	4,141.64LM	114.52LM/W	80	0.9	15%	72W – 80W
LOD-36WT88FTF-50KB	36W	4,247.61LM	117.24LM/W	80	0.9	15%	72W – 80W

Series	Wattage	CCT Options	Lens	Power
LOD-T88FT	36W	4000K 5000K	F = Frosted	B = Type B