


LED Premium Wrap

DIMENSIONS



APPLICATION

The LPW Series of LED Wraparound are a cost effective, energy-saving replacement for less efficient fluorescent wrap-around fixtures. The LPW wrap fixture features a full length U-wrap Acrylic lens and a one-piece fabricated steel body. These LED wraparound fixtures are ideal for lighting in parking garages, stairwells, and/or to help you meet applicable building and safety codes in residential multi-family buildings, workshops, utility rooms, corridors, and other commercial applications.

FEATURES

- Thermal/lumen balanced light engines
- Steel construction
- Back and end knockouts
- 4000 Kelvin Standard
- Low power consumption
- Can be ceiling or wall mounted
- For covered use only – damp rated
- Direct replacement of fluorescent Long life, 60,000 hour LEDs at L80 reduce lift cycle maintenance costs
- Battery backup available for emergency egress applications

HOUSING

Rugged construction, solid die formed, cold-rolled steel housing. All surfaces powder coated after fabrication. Frosted acrylic diffusers provides even consistent light while reducing glare.

MOUNTING

Suitable for surface mounting, suspension, or stem mounting, individually or in continuous rows.

ELECTRICAL

Equipped 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer. Long-Life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

WARRANTY

5-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

QUICK SHIP

LPW-9-40-MVD-840

ORDERING INFORMATION

Example Model Number: LPW-9-52-MVD-840-MOS

LPW	SIZE	WATTAGE	VOLTAGE	COLOR TEMPERATURE	OPTIONS
SERIES	9- 9" Width	40-40W-3500 Lumens ² 52-52W-4500 Lumens ^{1,2}	MVD- 120-277V; 0-10V Dimming ² HVD-347-480V,0-10V Dimming	840 - 80 CRI; 4000 Kelvin ² 850 - 80 CRI; 5000 Kelvin ¹	OS- 360 ° PIR Occupancy Sensor OSD- 360 ° PIR Occupancy Sensor w/ Daylight Sensor MOS- Integral Microwave Sensor FW3- 6', 3 Wire Fixture Whip FW4- 6', 4 Wire Fixture Whip EML8- Emergency Battery Pack, 800 Lumens EML14- Emergency Battery Pack, 1400 Lumens

Notes:
¹Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
²DLC Listed
³DLC Premium Listed