

WALL SCONCE
ML9 SERIES - LED INTEGRATED



Contemporary



ETL CLASSIFIED



Intertek



PRODUCT DESCRIPTION:

The LED Wall Sconces provides long-lasting illumination with a decorative touch to corridors in hotels, motels and commercial property applications. They offer long life, high lumen maintenance, and dimmable operation for residential and commercial applications that exceed those of a traditional bulb fixture.

FEATURES:

- Flicker free
- TRIAC dimming
- ENERGY STAR - ID#: 2255944

CONSTRUCTION:

- Die formed steel
- Powder coat
- High transmission glass (Contemporary style)

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

PRODUCT FAMILY	TYPE	OUTPUT	STYLE	FINISH	CCT/ CRI
ML9= Wall Sconces	LA= LED Integrated	17 = 17W	LCN= Contemporary, 8"	BNI= Brushed Nickel	927= 2700K, 90 CRI

DIMMER SELECTION LIST:

DIMMING INPUT VOLTAGE	DIMMER MODEL	MANUFACTURER	DIMMING TYPE	RATED INPUT VOLTAGE FOR DIMMER (V)	RATED POWER FOR DIMMER (W)
120V	S-600P	Lutron	Triac (LE) Incan	120VAC	600
	SELV-300P	Lutron	ELV (TE)		300
	CTCL-153P	Lutron	Triac (LE) Incan		600
	TGCL-153P	Lutron	Triac (LE) Incan		600
	6631	Lutron	Triac (LE) Incan		600
	SCL-153P	Lutron	Triac (LE) Incan		600
230V	AWSMG-EAW	Leviton	ELV (TE)	230VAC	600/1150/1385
	AWSMG-MAW	Leviton	MLV (LE) Incan		600/1150/1385
277V	6631	Leviton	MLV (TE)	277AC	600/1150/1385
	6631	Leviton	Triac (LE) Incan		1385

SPECIFICATIONS:

ORDER CODE: 77655
ML9LA17LCNBNI927

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Color Temperature (CCT)	2700K
	Delivered Lumens	1550 lm
	Efficacy (lm/W)	88 lm/W
	Lumen Maintenance (L70)	50,000 Hrs
ELECTRICAL	Input Voltage	120V, 60 Hz - Triac dimming
	Compatible Dimmers	See list of compatible dimmers
	Power Consumption	17W
PHYSICAL	Dimensions	13.375" W x 7.875" H x 3" D
	Power Factor	>0.90
	Operating Temperature	-4°F-113°F (-20°C-45°C)
CERTIFICATION	Certification	cULus, Energy Star, FCC
	Environment	Suitable for damp, install using only Class 2 power supply
	Warranty	5-year standard warranty*