

PROJECT NAME:	_CATALOG NUMBER:	
NOTES:	FIXTURE SCHEDULE:	

Page: 1 of 2

## T20 JA8 A LAMP LED OMNI-DIRECTIONAL

A19 / E26 BASE



#### PRODUCT DESCRIPTION:

MaxLite's LED enclosed rated Omnidirectional A-Line lamp replicate true A19 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.























#### **FEATURES:**

- T20 and JA8 Listed
- Beam Angle 220°
- · Suitable for use in enclosed luminaires
- Suitable for damp locations
- Triac dimmable 10%-100%

### **WARRANTY:**

5-year standard warranty (further details available at www.maxlite.com/warranties)

### **ORDER STRUCTURE**

FAMILY	DIMMABLE	CRI, COLOR TEMPERATURE AND GENERATION
E5.5A19= Enclosed Rated 5.5W A19 E9A19= Enclosed Rated 9W A19 E11A19= Enclosed Rated 11W A19	<b>D=</b> Dimmable	927/JA8S1= 90CRI, 2700K, JA8 Listed, Gen 1 930/JA8S1= 90CRI, 3000K, JA8 Listed, Gen 1 940/JA8S1= 90CRI, 4000K, JA8 Listed, Gen 1

#### **ORDER TABLE**

ORDER CODE	MODEL NUMBER	ENERGY STAR ID	HEIGHT (IN)	WIDTH (IN)	QTY IN CASE
108948	E5.5A19D927/JA8S1	2400216	4.07""	2.36"	50pcs
108949	E5.5A19D930/JA8S1	2400217	4.07"	2.36"	50pcs
108950	E5.5A19D940/JA8S1	2400218	4.07"	2.36"	50pcs
108951	E9A19D927/JA8S1	2400233	4.29"	2.36"	50pcs
108952	E9A19D930/JA8S1	2400234	4.29"	2.36"	50pcs
108953	E9A19D940/JA8S1	2400235	4.29"	2.36"	50pcs
108954	E11A19D927/JA8S1	2400263	4.55"	2.36"	50pcs
108955	E11A19D930/JA8S1	2400264	4.55"	2.36"	50pcs
108956	E11A19D940/JA8S1	2400265	4.55"	2.36"	50pcs

**MaxLite** 



# T20 JA8 A LAMP LED OMNI-DIRECTIONAL A19 / E26 BASE

Page: 2 of 2

SPECIFICATIONS		E5.5A19D9XX/JA8S1	E9A19D9XX/JA8S1	E11A19D9XX/JA8S1	
ITEM	SPECIFICATION	DETAILS			
	Power Consumption (W)	5.5	9	11	
	Lumens Delivered (Im)	450	800	1100	
	Equivalency	40W Inc.	60W Inc.	75W Inc.	
	Efficacy (Im/W)	≥89	≥90	≥100	
GENERAL PERFORMANCE	Distribution	220°			
	CRI	≥90			
	Color Temperature (K)	2700K, 3000K, 4000K			
	Lumen Maintenance	25,000 Hours			
	Dimmability	Triac 10%-100%			
ELECTRICAL	Power Factor	≥0.9 120V 60Hz			
ELECTRICAL	Input Voltage				
	Base Type	E26  Polycarbonate  -4°F to 113°F (-20 to 45°C)			
PHYSICAL	Lens				
PHYSICAL	Operating Temperature				
Piece per carton		50 pcs			
	Certification	cETLus listed, FCC, ES Listed, T20 Listed, JA8-2019-E, RoHS  Damp Locations, Enclosed Luminaires, Recessed Luminaires			
QUALIFICATION	Environment			sed Luminaires	
	Warranty	5 year warranty			

#### **COMPATIBLE DIMMERS:**

MANUFACTURE	DIMMERS PART #
LUTRON	TGCL-153P
	DVCL-153P
	CTCL-153P
	MAELV-600
LEVITON	6674

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

PLM731