

# **NYELXTEU**

# NEW YORK CITY COMPLIANT EDGELIT ALUMINUM EXIT SIGN

STANDARD

**OPTIONAL** 















# ILLUMINATION

- Ultra bright, energy efficient, long life Red LEDs.
- UV-stabilized ultra-clear acrylic edgelit panel provides consistent, uniform illumination.
- Double face utilizes factory installed silver or white mylar background panel.
- New York City compliant 8" EXIT letters.

# **ELECTRICAL**

- Dual 120/277 voltage standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### **MOUNTING**

Aluminum mounting canopy included for top, end or back mount.
Available in optional black or white powder-coated finishes.

# HOUSING

- Premium-grade, extruded aluminum housing (also available in black or white powder-coated finishes).
- Self-adhesive Chevron appliques and guide template provided for directional indication.


#### **OPTIONS**

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- SPV: UL Listed for 208/220/240 Volt, 50/60Hz.

#### **WARRANTY / LISTING**

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C − 50°C).
- Certified to CEC under Title 20 Regulations.

#### **DIMENSIONS**



#### **ORDERING INFORMATION**

Sample Part Number: NYELXTEU1RCAEM

	MODEL	No. of FACES		LETTER COLOR		PANEL		HOUSING COLOR		BATTERY		OPTIONS	
	NYELXTEU	1	Single Face	R	Red	С	Clear 1	W	White	(blank)	AC-Only	SDT	Self-Diagnostics <sup>2</sup>
<sup>1</sup> With single face only.		2	Double Face			Μ	Mirror	В	Black	EM	Battery	SPV	208/220/240
<sup>2</sup> Available only with EM units.						W	White	Α	Aluminum		Backup		Volt, 50/60Hz <sup>3</sup>
3 Not available with SDT		l		l		٠.	********		1	I		l I	