

		LED Ceiling Fixture ø 15X4" for MPLR, Fabric, PMMA diffuser(21358-BP6)		Item # 829	
1 FIXTURE SPECIFICATION					
1-1	Fixture Type	Celing Fixture			
1-2	Dimmable (Y/N)	SCR, Digital			
1-3	Fixture Finish/Type	Empty Fixture			
1-4	Fixture Wattage (*Variable)	16/19/25W			
1-5	Color	Brushed Nickel			
1-6	LED Type	Module			
1-7	Body Materials	Fabric			
2-1	Diffuser	PMMA			
2-2	Finishing Type	Plating			
2-3	Color Temperature (*Variable)	3000K/4000K			
2-4	Color Rendering Index (CRI)	≥80		*Variable depends on type of Overdrive MPLR used	
3 Electrical Characteristics					
3-1	Input Line Voltage/Frequency	120V	3-4	Power Factor	>090
3-2	Lamp rated Wattage	16W or 19 or 25W	3-5	Dimming Type	Dimmable
3-3	Total Harmonic Distortion	<40%			
4 Dimensional Characteristics					
4-1	Width (Inch)	4.02			
4-2	Height(Inch)	15			
5 Product Information					
5-1	Primary Application	Residential/Hospitality			
5-2	Limited Warranty	5 Years from date of purchase			
5-3	Certified	ETL/ES/LM79 with Overdrive MPLR			
5-4	RoHS Compliant	Yes			
5-5	Environment	Suitable for Damp Location/Indoor Use			
6 Packing Details					
6-1	Master Carton Size	22.88x13.78x13.78	6-3	N.W.(Kg)	3.80
6-2	Qty /Box	6 pcs	6-4	G.W.(Kg)	5.10
07/2018© Overdrive For more information visit www.overdrive-lighting.com					
Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.					