

LED Ceiling Fixture ø 11.2X3" for MPLR, PMMA diffuser(21415-MN-BP6) PMMA diffuser(21415-MN-BP6)

Item # 832

1	FIXTURE SPECIFICATION			
1-1	Fixture Type	Celing Fixture		
1-2	Dimmable (Y/N)	SCR, Digital		
1-3	Fixture Finish/Type	Empty Fixture		
1-4	Fixture Wattage (*Variable)	16/19/25W		
1-5	Color	Sliver		"
1-6	LED Type	Module		
1-7	Body Materials	Aluminum		
2-1	Diffuser	PMMA		
2-2	Finishing Type	Plating		
2-3	Color Temperature (*Variable)	3000K/4000K	*Variable o	depends on type of
2-4	Color Rendering Index (CRI)	≥80	Overdr	ive MPLR used
3	Electrical Characteristics			
3-1	Input Line Voltage/Frequency	120V	3-4 Power Factor	>090
3-2	Lamp rated Wattage	16W or 19 or 25W	3-5 Dimming Type	Dimmable
3-3	Total Harmonic Distortion	<40%		
4	Dimensional Characteris	tics		
4-1	Width (Inch)	2.95		
4-2	Height(Inch)	11.1		
5	Product Information			
5-1	Primary Application	Residential/Hospitality		
5-2	Limited Warranty	5 Years from date of purchase		
5-3	Certified	ETL/ES/LM79 with Overdrive MPL	R	
5-4	RoHS Compliant	Yes		
5-5	Environment	Suitable for Damp Location/Indoo	or Use	
6	Packing Details			
6-1	Master Carton Size	20.28x12.4x12.4 6-3	N.W. (Kg)	2.30
6-2	Qty /Box	6 pcs 6-4	G.W. (Kg)	3.30
07/2018© Overdrive For more information visit www.overdrive-lighting.com Note: This data sheet is not controlled copy & is subject to change without notice. Standard Tolerances apply on data given above.				