



RP

LIGHTING • FANS

Type:
Project:
Comments:
Prepared By:

Remote head options	
RH21	Single remote head (Wide focal)
RH21-N	Single remote head (narrow focal)
RH22	Double remote head (Wide focal)
RH22-N	Double remote head (narrow focal)

Category #:	REL22 (Wide focal lens) REL22-N (Narrow focal lens)
Description:	High output LED Emergency Light w/ remote head capability
Finish	White

Design Features	
Housing	Damp location listed made of high-impact thermoplastic and flame retardant housing.
Operating Temp.	50° F to 104° F
	Completely Self-contained
Mounting	Ceiling and wall mountable
Wattage	4W
Voltage	120/277V
Test switch	Momentary test switch included
Lamp	Adjustable LED heads
Charging	Fully automatic operation w/integral recharging system
Battery	One Ni Cad rechargeable battery w/ expected life of 10 years.
Lens Material	Clear Plastic
Frame Material	Thermoplastic & flame retardant

Listing	
ETL/UL	cULus listed for damp location
Additional features	Protected from deep discharge by automatic low voltage disconnect circuitry. Whenever normal AC current fails, the integral state transfer switches automatically connects the internal battery to the fixture to keep the sign illuminated for at least 90 minutes

