

# RT Series

## LED Re-trofit Kits for Troffers



### Features

#### Housing

Aluminum Extrusion Housing with Easy Mounting Bracket  
Magnet Construction Makes Easy Pre-alignment on Installation

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

#### Electrical

120V – 277V

#### Lamp

Built-in LED Module  
Dimming Option: 0-10V Dimming

#### Certification

ETL/cETL Listed, DLC Listed

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Re-trofit Kits

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT / CRI	Dimension (L X W X H)	DLC
RT-2x2-2L-HO-4000K	120V ~ 277V	19W	1870	4100K / 80	20.7" x 1.0" x 0.8"	Standard
RT-2x2-2L-HO-5000K	120V ~ 277V	19W	1910	5000K / 80	20.7" x 1.0" x 0.8"	Standard
RT-2x2-3L-HO-4000K	120V ~ 277V	29W	2900	4100K / 80	20.7" x 1.0" x 0.8"	Standard
RT-2x2-3L-HO-5000K	120V ~ 277V	29W	3000	5000K / 80	20.7" x 1.0" x 0.8"	Standard
RT-2x4-2L-HO-4000K	120V ~ 277V	37W	3780	4100K / 80	44.2" x 1.0" x 0.8"	Standard
RT-2x4-2L-HO-5000K	120V ~ 277V	37W	3820	5000K / 80	44.2" x 1.0" x 0.8"	Standard
RT-2x4-3L-HO-4000K	120V ~ 277V	55W	5760	4100K / 80	44.2" x 1.0" x 0.8"	Standard
RT-2x4-3L-HO-5000K	120V ~ 277V	55W	5800	5000K / 80	44.2" x 1.0" x 0.8"	Standard
RT-2x2-2L-VHO-4000K	120V ~ 277V	16W	2050	4100K / 80	20.7" x 1.0" x 0.8"	Premium
RT-2x2-2L-VHO-5000K	120V ~ 277V	16W	2120	5000K / 80	20.7" x 1.0" x 0.8"	Premium
RT-2x2-3L-VHO-4000K	120V ~ 277V	23W	2950	4100K / 80	20.7" x 1.0" x 0.8"	Premium
RT-2x2-3L-VHO-5000K	120V ~ 277V	23W	3000	5000K / 80	20.7" x 1.0" x 0.8"	Premium
RT-2x4-2L-VHO-4000K	120V ~ 277V	30W	3860	4100K / 80	44.2" x 1.0" x 0.8"	Premium
RT-2x4-2L-VHO-5000K	120V ~ 277V	30W	3960	5000K / 80	44.2" x 1.0" x 0.8"	Premium
RT-2x4-3L-VHO-4000K	120V ~ 277V	46W	6030	4100K / 80	44.2" x 1.0" x 0.8"	Premium
RT-2x4-3L-VHO-5000K	120V ~ 277V	46W	6200	5000K / 80	44.2" x 1.0" x 0.8"	Premium