

3-4048

Wall Mount, Down Light, Outdoor, Wet Location



Features

Housing

Die-cast Aluminum with Powder Coated Finish
 Finish Options: -05 Black, -30 Oil Rubbed Bronze
 Good for Wet Location Applications

Optical

Shade: Clear Glass

Electrical

120V – 277V, Built-in Photo Cell Option
 High Power Factor, Low THD

Lamp


Integrate LED Module: Color Temperature Option 3000K, 3500K, 4000K, 5000K

Certification

ETL/cETL Listed, Suitable for Wet Locations, CEC Listed

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish	Dimension (L x W X E)	Energy Star
3-4048D-30-xxxxK	120V ~ 277V	9W	3000K / >80	750	Oil Rubbed Bronze	8.0" x 4.5" x 7.0"	Yes

JA8 Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish	Dimension (L x W X E)	Energy Star	CEC Listed
3-4048D-30 (JA8)	120V	8.5W	3000K / >90	790	Oil Rubbed Bronze	8.0" x 4.5" x 7.0"	Yes	Yes

Note: LED Driver, 120V Triac Dimming