

60-18W 60-36W 72-18W 72-36W

LED Refrigerated Case Light and Display Case Light



Features

Housing

Aluminum Extrusion, Vapor Tight

Optical

Shade: Clear Polycarbonate Tube

Adjustable Light Direction, Offers Even Light

Electrical

LED driver: 120V ~ 277V, Class 2, 24V DC, Constant Voltage, 100W, Power Factor >0.9, THD <20%, Minimum Starting Temperature: -30°C

Lamp

Integrated Linear LED Module

Certification

ETL/cETL

Warranty

5 Years Limited Warranty



Single Light

Model	Input Voltage	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
60-18W	120V ~ 277V	DC 24V	18W	5000K	>80	1540	57.0" x 1.2" x 1.1"	---
72-18W	120V ~ 277V	DC 24V	18W	5000K	>80	1540	69.0" x 1.2" x 1.1"	---

Double Light

Model	Input Voltage	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
60-36W	120V ~ 277V	DC 24V	36W	5000K	> 80	3080	57.0" x 2.2" x 1.1"	---
72-36W	120V ~ 277V	DC 24V	36W	5000K	> 80	3080	69.0" x 2.2" x 1.1"	---