

BH24 BH48

Vapor Tight



Features

Housing

Injection Molded Polycarbonate Housing with Die-formed Cold-rolled Steel Reflector
Injection Molded Polycarbonate Shade
Stainless Steel Clips
Ideal for Harsh Environment Applications
Suitable for Ceiling Mount or Suspended Mount

Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity
DLC Listed LED T8 Tube Efficacy > 100 lm/W

Electrical

Built-in Constant Current LED Driver with High efficient LED Module

Lamp

LED Type: LED T8 Tube, UL Listed
CFL Type: T8 or T5 Tube

Certification

LED Fixtures: ETL/cETL Listed
T8 & T5 HO Lamp Fixtures: UL/cUL Listed



LED Type

Model	Input Voltage	Input Wattage	T8 LED Tube	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)
BH24D-20W-4000K	120V ~ 277V	20W	2 x 10W	4000K	80	1980	26.5" x 6.5" x 4.5"
BH24D-20W-5000K	120V ~ 277V	20W	2 x 10W	5000K	80	2060	26.5" x 6.5" x 4.5"
BH48D-36W-4000K	120V ~ 277V	36W	2 x 18W	4000K	80	3565	50.0" x 6.5" x 4.5"
BH48D-36W-5000K	120V ~ 277V	36W	2 x 18W	5000K	80	3670	50.0" x 6.5" x 4.5"
BH48D-44W-4000K	120V ~ 277V	44W	2 x 22W	4000K	80	4355	50.0" x 6.5" x 4.5"
BH48D-44W-5000K	120V ~ 277V	44W	2 x 22W	5000K	80	4490	50.0" x 6.5" x 4.5"

T8 & T5 HO Lamp Type

Model	Input Voltage	Input Wattage	Reflector	Lamp	Shade	Dimension (L X W X H)
BH24-217	120V ~ 277V	34W	White	2 x F17T8, 17W	Polycarbonate	26.5" x 6.5" x 4.5"
BH48-132	120V ~ 277V	32W	White	1 x F32T8, 32W	Polycarbonate	50.0" x 4.0" x 4.5"
BH48-232	120V ~ 277V	56W	White	2 x F32T8, 32W	Polycarbonate	50.0" x 6.5" x 4.5"
BH48-254	Programmable Start Ballast 120V ~ 277V	110W	White	2 x F54T5HO, 54W	Polycarbonate	50.0" x 6.5" x 4.5"