

BH48D-72W BH48-432

4 Lamps Vapor Tight



Features

Housing

Aluminum Die Casting and Extrusion with High Reflection Type Aluminum Reflector
 Stainless Steel Clips
 Ideal for Harsh Environment Applications
 Suitable for Ceiling Mount or Suspended Mount

Optical

Shade: Injection Molded High Transmission Polycarbonate

Electrical

T8 CFL Type with High Ballast Factor Ballast to Maximize Light Output

Lamp

LED Type: DLC Listed LED T8 Tube, UL Listed
 CFL Type: T8 Tube

Certification

LED Fixtures: ETL/cETL Listed
 T8 CFL Fixtures: UL/cUL Listed, T8 Ballast with NEMA and CEE Listed



LED Type

Model	Input Voltage	Input Wattage	T8 LED Tube	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)
BH48D-72W-4000K	120V ~ 277V	72W	4 x 18W	4000K	80	8500	50.2" x 12.2" x 4.0"
BH48D-72W-5000K	120V ~ 277V	72W	4 x 18W	5000K	80	8500	50.2" x 12.2" x 4.0"

T8 Lamp Type

Model	Input Voltage	Input Wattage	Reflector	Lamp	Shade	Dimension (L X W X H)
BH48-432	120V ~ 277V	145W	Specular reflector	4 x F32T8, 32W	Polycarbonate	50.2" x 12.2" x 4.0"