

# BH24DX BH48DX

## LED Vapor Tight



### Features

#### Housing

Injection Molded Polycarbonate  
 Stainless Steel Clips  
 Ideal for Harsh Environment Applications  
 Suitable for Ceiling Mount or Suspended Mount

#### Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity  
 High Luminous Efficacy > 100lm/W

#### Electrical

Built-in Constant Current LED Driver with High efficient LED Module  
 Bi-Level Light Option - with Built-in Motion Sensor  
 Emergency Back Up Option - Built-in Emergency Battery Back Up

#### Lamp

Built-in LED Module

#### Certification

ETL/cETL Listed, DLC Listed, IP65 Rated

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
BH24DX-16W-4000K	120V ~ 277V	16W	4000K	> 80	1870	26.5" x 4.3" x 2.4"	---
BH24DX-16W-5000K	120V ~ 277V	16W	5000K	> 80	2000	26.5" x 4.3" x 2.4"	---
BH48DX(4000K)	120V ~ 277V	33W	4000K	> 80	3480	50.0" x 4.3" x 2.4"	Standard, 5.1
BH48DX(5000K)	120V ~ 277V	33W	5000K	> 80	3740	50.0" x 4.3" x 2.4"	Standard, 5.1
BH24DX-HE-4000K	120V ~ 277V	23W	4000K	> 80	2510	26.5" x 4.3" x 2.4"	---
BH24DX-HE-5000K	120V ~ 277V	23W	5000K	> 80	2560	26.5" x 4.3" x 2.4"	---
BH48DX-HE(4000K)	120V ~ 277V	45W	4000K	> 80	4950	50.0" x 4.3" x 2.4"	Standard, 5.1
BH48DX-HE(5000K)	120V ~ 277V	45W	5000K	> 80	4950	50.0" x 4.3" x 2.4"	Standard, 5.1
BH24DX-VHO-4000K	120V ~ 277V	14.5W	4000K	> 80	1880	26.5" x 4.3" x 2.4"	---
BH24DX-VHO-5000K	120V ~ 277V	14.5W	5000K	> 80	1900	26.5" x 4.3" x 2.4"	---
BH48DX-VHO-4000K	120V ~ 277V	29W	4000K	> 80	3760	50.0" x 4.3" x 2.4"	---
BH48DX-VHO-5000K	120V ~ 277V	29W	5000K	> 80	3760	50.0" x 4.3" x 2.4"	---