

Features

Housing

Low Profile with Polycarbonate, Suitable for Tight Space

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

Electrical

Power Cord Included. Linkable Cable Sold Separately

Operation Temperature: 32F ~ 104F

Lamp


Linkable LED Type: Built-in LED Strip

LED: High Efficiency, High CRI (> 80), Binned and Mixed to Reach Uniform Light

Linkable LED Type, Color Temperature 3000K, 5000K

Certification

ETL/cETL Listed



Linkable LED Type

Model	Input Voltage	Input Wattage	Lumen	LED/CT	Housing/Shade	Dimension (L X W X H)
C004-51	120V	4W	360	5000K	PC / Acrylic	13.5" x 0.9" x 1.7"
C007-51	120V	7W	630	5000K	PC / Acrylic	22.5" x 0.9" x 1.7"
C008-51	120V	8W	720	5000K	PC / Acrylic	23.7" x 0.9" x 1.7"
C014-51	120V	14W	1260	5000K	PC / Acrylic	35.6" x 0.9" x 1.7"
C018-51	120V	18W	1620	5000K	PC / Acrylic	47.4" x 0.9" x 1.7"

Linkable Cables

Model	Length	Note
C51-6	6"	LED Type
C51-12	12"	LED Type
C51-18	18"	LED Type
C51-24	24"	LED Type

J-Box

Model	Dimension (L X W X H)	Note
J-BOX	4.0" x 2.2" x 1.5"	C0xx-51 Series