

# DC818D-B DC818D-B-PD

## Ceiling Fixture & Pendant



### Features

#### Housing

Die-formed Cold-rolled Steel  
 Finish Option: -06 White, -30 Oil Rubbed Bronze, -05 Black  
 Low Profile Design

#### Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity  
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Lamp

Built-in LED Module, Color Temperature Option: 3000K or 4000K  
 MCT Type: Tunable Color Temperature (3000K, 4000K, 5000K) with Slide Switch

#### Certifications

ETL/cETL Listed

#### Warranty

5 Years Warranty on Driver and LED Module



### LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (Typ)	LED CT	Finish	Shade	Dimension (OD X H)
DC818D-B-xxxxK-06	120 - 277V	35W	> 80	3200	3000K or 4000k	White	Acrylic / Linen	20.8" x 3.6"
DC818D-B-MCT-06	120 - 277V	35W	> 80	3200	3000K / 4000k / 5000K	White	Acrylic / Linen	20.8" x 3.6"

### Pendant LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (Typ)	LED CT	Finish	Shade	Dimension (OD X H x H1)
DC818D-B-PD-xxxxK-06	120 - 277V	35W	> 80	3200	3000K or 4000K	White / (canopy) Satin Nickel	Acrylic / Linen	20.8" x 3.6" x 6'
DC818D-B-PD-MCT-06	120 - 277V	35W	> 80	3200	3000K / 4000K / 5000K	White / (canopy) Satin Nickel	Acrylic / Linen	20.8" x 3.6" x 6'

H1: Hanging Cable Length, 6ft max.