

ECO12D ECO14D ECO18D

Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel
 Low Profile Design
 Finish Options: -62 Satin Nickel, -30 Oil Rubbed Bronze, -05 Black
 -PD: Available Pendant Models

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor (> 0.95), Low THD (< 20%)
 Dimmable with LED Triac Dimmer

Lamp


Built-in LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.
 Color Temperature Option – 3000K, 4000K
 MCT Type: Get Preferable Fixture Color Temperature by Slide Switch on LED Board
 Color Temperature Option – 3000K, 3500K, 4000K

Certifications

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Finish	Shade	Dimension (OD X H)	Energy Star
ECO12D-12W-xxxxK-62	120V	12W	580	3000K or 4000K	> 80	Satin Nickel	Acrylic	11.8" x 3.2"	Yes
ECO12D-xxxxK-62	120V	18W	960	3000K or 4000K	> 80	Satin Nickel	Acrylic	11.8" x 3.2"	Yes
ECO14D-MCT-62	120V	25W	1350	3000K, 3500K, 4000K	> 80	Satin Nickel	Acrylic	14.5" x 3.5"	Yes
ECO18D-MCT-62	120V	32W	1700	3000K, 3500K, 4000K	> 80	Satin Nickel	Acrylic	17.8" x 4.0"	Yes