

HB12D HB15D HB16D HB17D

LED High Bay



Features

Housing

Die-formed Cold-rolled Steel and V Hook & Hanging Chain Included
Eco-frame & full Body Linear Construction

Optical

High Lumen Efficiency and High CRI LED
High Transmission Acrylic Shade

Electrical

UL2459 / CSA182.3 Power Connector Included

Lamp

Integrate LED Module with High CRI
Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED

Options

-LS with Lens -Bi with Bi-Level Light
-EM with Emergency Driver (Built-in or External EM Driver)



High Light Output Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)
HB12D-85W-VHO-4000K	120V ~ 277V	81W	4000K	80	11240	21.0" x 16.0" x 1.5"
HB12D-85W-VHO-5000K	120V ~ 277V	81W	5000K	80	11490	21.0" x 16.0" x 1.5"
HB12D-105W-VHO-4000K	120V ~ 277V	101W	4000K	80	14200	21.0" x 16.0" x 1.5"
HB12D-105W-VHO-5000K	120V ~ 277V	101W	5000K	80	14550	21.0" x 16.0" x 1.5"
HB15D-130W-VHO-4000K	120V ~ 277V	125W	4000K	80	17600	21.0" x 20.0" x 1.5"
HB15D-130W-VHO-5000K	120V ~ 277V	125W	5000K	80	17760	21.0" x 20.0" x 1.5"
HB16D-170W-VHO-4000K	120V ~ 277V	165W	4000K	80	22980	43.0" x 16.0" x 1.5"
HB16D-170W-VHO-5000K	120V ~ 277V	165W	5000K	80	23060	43.0" x 16.0" x 1.5"
HB16D-210W-VHO-4000K	120V ~ 277V	205W	4000K	80	28950	43.0" x 16.0" x 1.5"
HB16D-210W-VHO-5000K	120V ~ 277V	205W	5000K	80	29400	43.0" x 16.0" x 1.5"
HB17D-253W-VHO-4000K	120V ~ 277V	244W	4000K	80	34650	43.0" x 20.0" x 1.5"
HB17D-253W-VHO-5000K	120V ~ 277V	244W	5000K	80	34950	43.0" x 20.0" x 1.5"
HB17D-340W-VHO-4000K	120V ~ 277V	323W	4000K	80	45770	43.0" x 20.0" x 1.5"
HB17D-340W-VHO-5000K	120V ~ 277V	323W	5000K	80	46220	43.0" x 20.0" x 1.5"