

HB5D HB6D HB8D

LED High Bay



Features

Housing

Die-formed Cold-rolled Steel and V Hook & Hanging Chain Included
Eco-frame & full Body Linear Construction

Optical

High Lumen Efficiency and High CRI LED
High Transmission Acrylic Shade

Electrical

UL2459 / CSA182.3 Power Connector Included

Lamp

Integrate LED Module with High CRI
Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED

Options

-LS with Lens -Bi with Bi-Level Light
-EM with Emergency Driver (Built-in or External EM Driver)



Standard Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)
HB5D-110-HE(4000K)	120V ~ 277V	110W	4000K	80	12990	21.5" x 11.8" x 2.0"
HB5D-110-HE(5000K)	120V ~ 277V	110W	5000K	80	14680	21.5" x 11.8" x 2.0"
HB6D-160-HE(4000K)	120V ~ 277V	165W	4000K	80	19450	21.5" x 16.0" x 2.0"
HB6D-160-HE(5000K)	120V ~ 277V	165W	5000K	80	22020	21.5" x 16.0" x 2.0"
HB8D-220-HE(4000K)	120V ~ 277V	220W	4000K	80	28600	43.0" x 11.8" x 2.0"
HB8D-220-HE(5000K)	120V ~ 277V	220W	5000K	80	29370	43.0" x 11.8" x 2.0"

Premium Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)
HB5D-92W-VHO-4000K	120V ~ 277V	92W	4000K	80	11730	21.5" x 11.8" x 2.0"
HB5D-92W-VHO-5000K	120V ~ 277V	92W	5000K	80	11970	21.5" x 11.8" x 2.0"
HB6D-140W-VHO-4000K	120V ~ 277V	140W	4000K	80	17700	21.5" x 16.0" x 2.0"
HB6D-140W-VHO-5000K	120V ~ 277V	140W	5000K	80	18200	21.5" x 16.0" x 2.0"
HB8D-185W-VHO-4000K	120V ~ 277V	185W	4000K	80	24030	43.0" x 11.8" x 2.0"
HB8D-185W-VHO-5000K	120V ~ 277V	185W	5000K	80	24500	43.0" x 11.8" x 2.0"