

# MDF039

## Wall Sconce



### Features

#### Housing

Die-formed Cold-rolled Steel

Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD

#### Lamp

LED Type: Integrate LED Module , 3000K LED


More Color Temperature Option 3500K, 4000K, 5000K

GU24 Type: - CFL Bulb, 2700K or 4000K

- 9W LED Bulb, 3000K or 4000K

#### Certification

ETL/ETL Listed, Suitable for Damp Locations



### LED Type

Model	Input Voltage	Input Wattage	CT	Lumen (Typ)	Finish	Dimension (W x H x D)	Energy Star
MDF039D-xxxxK-62	120V-277V	14W	3000K	1360	Satin Nickel	16.0" x 7.9" x 4.0"	Yes

### CFL Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H x D)	Energy Star
MDF039-213	120V	2x13W GU24	Satin Nickel	Acrylic	16.0" x 7.9" x 4.0"	---