

P3234D P3246D

Ceiling Fixture & Pendant



Features

Housing

Aluminum Extrusion
 Finish Option: -60 Brushed Aluminum, -30 Oil Rubbed Bronze, -05 Black
 Pendant Mount by 6 Feet Hanging cable

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD
 Bi-Level Lighting and Emergency Backup Model available

Lamp


LED Type: Built-in (Multiple Color Temperature Option – 3000K, 3500K, 4000K)

Certifications

ETL/cETL Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (Typ) / CT	Finish	Shade	Dimension (L x W x H)
P3234D-PD-MCT-30	120V ~ 277V	36W	> 80	3000 / 3000K, 3500K, 4000K	Oil Rubbed Bronze	Acrylic	34.0" x 8.9" x 2.8"
P3246D-PD-MCT-30	120V ~ 277V	50W	> 80	4000 / 3000K, 3500K, 4000K	Oil Rubbed Bronze	Acrylic	46.0" x 8.9" x 2.8"

Hanging Cable Length (H1): 6', Adjustable