

Overbed Light

Features

Housing

Die-formed Cold-rolled Steel and Aluminum

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.

Electrical

High Power Factor, Low THD

Lamp

LED Module: Multiple Color Temperature Type (MCT, Adjustable, 3000K/3500K/4000K)

Certification

ETL/cETL Listed, Damp Rated

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT	Lumen (TYP)	Finish	Shade	Dimension (L X H X E)
V6822D-MCT-BDL-60/05	120V – 277V	30W	3000K/3500K/4000K	1750	Brushed Aluminum / Black	Acrylic	23.8" x 4.3" x 2.3"
V6834D-MCT-BDL-60/05	120V – 277V	34W	3000K/3500K/4000K	2000	Brushed Aluminum / Black	Acrylic	35.8" x 4.3" x 2.3"
V6846D-MCT-BDL-60/05	120V – 277V	40W	3000K/3500K/4000K	2350	Brushed Aluminum / Black	Acrylic	47.8" x 4.3" x 2.3"