

# W190D W190D-L

## Wall Sconce



### Features

#### Housing

Die-formed Cold-rolled Steel  
Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity  
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD  
-EM: Built-in Emergency Light

#### Lamp


Integrate LED Module , Color Temperature Option 3000K, 3500K, 4000K, 5000K

#### Certification

ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Limited Warranty on Driver and LED



### LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Shade	Dimension (H x W x D)	Energy Star
W190D-xxxxK	120V-277V	15W	3000K	>80	1025	Acrylic	15.0" x 5.0" x 4.0 "	---
W190D-EM-xxxxK	120V-277V	15W	3000K	>80	1025	Acrylic	15.0" x 5.0" x 4.0"	---
W190D-L-xxxxK	120V-277V	23W	3000K	>80	1550	Acrylic	24.0" x 5.0" x 4.0"	---
W190D-EM-L-xxxxK	120V-277V	23W	3000K	>80	1550	Acrylic	24.0" x 5.0" x 4.0"	---