

WP7-A WP8-A WP9-A

Wall Pack, Outdoor



Features

Housing

Die-formed Cold-rolled Steel with Epoxy Powder Coated Finish

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

120V – 277V, Photo Cell Option

Lamp

Integrate LED Module

More Color Temperature Option 4000K

Certification


ETL/cETL Listed, Suitable for Wet Locations

Warranty

5 Years Limited Warranty on Driver and LED

Options

- Bi Bi-Level Light Option
- EM Emergency Backup Light Option



LED Type

| Model | Input Voltage | Input Wattage | LED CT | CRI | Lumen (TYP) | Finish | Shade | Dimension (L x W X D) |
|--------------------|---------------|---------------|--------|------|-------------|--------|---------|-----------------------|
| WP7-A-05-15W-3000K | 120V ~ 277V | 15W | 3000K | > 80 | 665 | Black | Acrylic | 13.3" x 8.3" x 3.8" |
| WP8-A-05-23W-3000K | 120V ~ 277V | 23W | 3000K | > 80 | 1290 | Black | Acrylic | 21.7" x 8.3" x 3.8" |
| WP9-A-05-34W-3000K | 120V ~ 277V | 34W | 3000K | > 80 | 2110 | Black | Acrylic | 30.0" x 8.3" x 3.8" |

Order Code: -PC Photo Cell