



Project	
Notes	
Type	Date
Cat. No.	

**THF™ Series**

**Head Floodlight with Motion Sensor**



**DESCRIPTION**  
 Integrated long-life LED technology in an affordable, energy saving security lighting solution. Provides maintenance-free general and security illumination for outdoor use in residential and light commercial applications. Bright, uniform illumination is ideal for walkways, yards, patios, parking areas, driveways and egress easements creating an inviting exterior space as well as providing safety and security.

**Specification Features**

**Construction**  
 Two tool-free adjustable heads allow for easy aiming up/down or side to side. Rugged cast aluminum, corrosion-resistant housing in bronze or white. Clear acrylic lenses are fully gasketed to keep out moisture, dirt and bugs.

**Certification**  
 All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

**Warranty**  
 3-year Limited Warranty. See warranty documentation for more information.

**Electrical**  
 120V driver operates at 60Hz.

**Installation**  
 Mounts easily to existing junction box on wall or under building eave. Adjustable heads allow precise illumination. Not recommended to wire multiple fixtures in parallel.



**THF Series**  
 20W, 1440 Lumens

Rated Life 60,000 hours  
 Limited Warranty 3 years  
 Efficacy Up to 72 LPW  
 Continuous N/A



**Quick Ship**  
 Made to order only

**Ordering Information**

Example: THF-20-120-850-WH

THF	20	120	8	50	WH
<b>Series</b> THF Head Floodlight with Motion Sensor	<b>Rated Wattage</b> 20-20W, 1440 Lumens <sup>1</sup>	<b>Driver Type</b> 120-120V <sup>1</sup>	<b>CRI</b> 8 80+ CRI	<b>Color Temp</b> 40 4000 K <sup>1 2</sup> 50 5000 K <sup>1 2</sup>	<b>Color Temp</b> WH- White <sup>1</sup> ORB- Oil Rubbed Bronze <sup>1</sup>

Specifications and Dimensions subject to change without notice.

**Performance Summary**

Input Voltage	120V
Input Frequency	60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	> 72 LPW (typ.)
CRI	83+, R9 > 0
Available CCT <sup>1</sup>	5000K
Color Consistency <sup>2</sup>	5-step MacAdam Ellipse
Rated Life	60,000 hours
L70 <sup>3</sup>	> 72,000 hours or > 45,000
Power Factor	> 0.9
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

**Performance Data**

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
None	2'	THF-20-120-840-WH	20	1,440	72

NOTES:

- <sup>1</sup> Quick ship: Made to Order Only
- <sup>2</sup> Typical color consistency. May vary or be changed.
- <sup>3</sup> L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information



Specifications and Dimensions subject to change without notice.

Product Dimensions

THF-20

