

| | |
|------------|-------|
| Catalog #: | |
| Project : | |
| Type : | Date: |
| Notes: | |

T8/T5 Led Tube

TKIEO-2ST8/T5-4FT Series

DESCRIPTION

The T8/T5 Led Tube are the functional and multi-purpose channel family that incorporates premium performance and construction durability.

APPLICATIONS

This Luminaries widely used at garages, stairwells, storage areas and other wet and harsh environments.

Product Details

| Product ID | Materials | Wattage | Lm/W | CCT |
|-----------------------------|-----------|---------|---------|-----|
| TKIEO-2ST8/T5-4FT-6W-4K-F | PC cover | 6W | 170Lm/w | 4K |
| TKIEO-2ST8/T5-4FT-10W-4K-F | Glass | 10W | 180Lm/w | 4K |
| TKIEO-2ST8/T5-4FT-10W-4K-C | Glass | 10W | 180Lm/w | 4K |
| TKIEO-2ST8/T5-4FT-16W-4K-C1 | Glass | 16W | 180Lm/w | 4K |
| TKIEO-2ST8/T5-4FT-17W-5K-C | Glass | 17W | 180Lm/w | 5K |



Specification Features

Controls / Dimming

Aluminium body + PC cover Mount Ceiling Flicker Motion Sensor, Emergency Backup PIR sensor. 50,000 working hours

Warranty

5 Years Limited Warranty. See warranty documentation for more information.

Certification

It complies with 80+,ETL, CE, RoHS and 5 years warranty

Installation / Mounting

It is easy to install with the help of a universal mounting plate pre-installed at the bottom. Instant start w/NO humming. Optional surface or suspended mounted

Ordering Information

Example: TKIEO-2ST8/T5-4FT-6W-4K

| TKIEO | 2ST8/T5 | 4 | 6W | 4K | F |
|--------------|-------------------------|---------------|---|---|------------------------------------|
| Brand | Series | Length | Watts | Color | |
| TKIEO | 2ST8/T5 2 Side T8/T5 | 4FT 4 Feet | 6 W = 6 Watt 10 W = 10 Watt 16 W = 16 Watt 17W = 17 Watt | 4K - 4000K (Natural White) 5K - 5000K (Daylight White) | F = Frosted Lens C = Clear Lens |

Lighting Parameters

| | |
|---------------------|----------------------|
| Input Voltage | 100-277V AC |
| CRI | 140 to 80 |
| Luminous efficacy | Up to 180Lm/w |
| Beam Angle | 120° |
| Wattage | 6W / 10W / 16W / 17W |
| PF | >0.9 |
| Working temperature | -4°F - +122°F |
| Life span | 50,000 Hrs |

Product Dimension

