

# LED Shoe Box Light

Catalog #:	
Project :	
Туре :	Date:
Notes:	

# TK-SAL2

# DESCRIPTION

LED Shoebox light is perfect fixture for medium height parking lot poles an new construction applications in industrial, warehouse, manufacturing, commercial, office, residential, and hospitality facilities.

# **APPLICATIONS**

Ideal for lighting general outdoor, wet location and commercial area lightin (Replaces Metal Halide for superior energy efficiency and slim aesthetics.)



# Specification Features

# **Controls / Dimming**

High quality bi-level Motion sensor with increased energy savings (Optional) & Photocell

### Warranty

5 Years Limited Warranty. See warranty documentation for more information

# Certification

Wet Location Certified, safe and reliable. DLC Premium, UL certified.

# Installation / Mounting

Luminaire is easy to Surface Mount install. Five Mounting Options: Direct, Slip Fitter, Square/Round Pole Bracket, Trunnion and U bracket.

Ordering Info	rmation			Example: TK-SAL2-150W-YXX-P			
Fixture Type	Wattage	CRI	сст	Options	Voltage		
TK-SAL2 LED Shoe Box Light	60W 100W 120W 150W 200W 240W 300W	Y 7 - 70 8 - 80 9 - 90	XX 30 - 3000K 40 - 4000K 50 - 5000K 57 - 5700K	X Blank - Non-Dimmable D - Dimming P - Photocell M - Motion Sensor	Н Blank - 100 - 277V H - 200 - 480V		



Techno USA LLC dba Techno LED Lights 2763 Meadow Church Road, Suite 140, Duluth, GA-30097 | Tel: 678-456-4810 | Fax: 678-456-4810 | Email: sales@technoledlights.com TechnoLED™ is a registered trademark of Techno Electromech and Techno USA LLC. Specifications and Dimensions subject to change without notice. Atlanta | San Antonio | Los Angeles

# LED Shoe Box Light

Lighting Parameters	5	Dimensions	5					
Input Voltage	100-277VAC / 200-480VAC			f				ſ
ССТ	4000K,5000K, 5700K	[	336 [13.2]		139		336 [13.2]	
CRI	RA>70				[5.5]			
Lumen Efficiency	130lm/W							
Working temperature	-40°F~104°F	349 [13.7]			12	541 [[21.3]		
Power Factor	<u>&gt;</u> 0.95	[523] [518]				745 [29,3]		
Frequency	50/60 Hz		ĨĦĨ	Ø6 [2	8			Ø68 [2.7]
Lifetime	>50,000Hrs			78	3			78 [3.1]
Distribution	Type II/Type III/ Type IV/ Type V	ł	<u>                                   </u>	- [3	.13	ļ	<b>!</b> 200-300W	<u>140</u> _
Mounting Options								
			in the	C C		8		3
Direct (DI)	Slip Fitter	(SF)	Square/Ro	ound	Trunnio	n (TR)	U Bi	racket
Carrino -								
Microwave Motion Sensor	n Lightni	ng arrester	-	et base of notocell	Sh	orting Cap		otocell to dawn)
Input Voltage: 100-27	7VAC:	07 (0)	00 40000	05 (00)//	00 4 5000		07.04014	00.000
Model		SB-60W	SB-100W	SB-120W	SB-150W	SB-200W	SB-240W	SB-300W
Power Lumious Flux 130	m/\//	60W 7800LM	100W 13000LM	120W 15600LM	150W 19500LM	200W 26000LM	240W 31200LM	300W 39000LM
Replaces HID	111/ ••	180W	320W	400W	450W	600W	750W	1000W
LEDs Quantity		68	98	126	154	196	252	308
Input Voltage: 200-48 Model	BOVAC:	SB-HV-100W		SB-HV-150W		SB-HV-200W	/	SB-HV-300W
Power		100W		150W		200W		300W
Lumious Flux 130	m/W	13000LM		19500LM		26000LM		39000LM
Replaces HID		320W		450W		600W		1000W
LEDs Quantity		98		154		196		308

Techno USA LLC dba Techno LED Lights 2763 Meadow Church Road, Suite 140, Duluth, GA-30097 | Tel: 678-456-4810 | Fax: 678-456-4810 | Email: sales@technoledlights.com TechnoLED™ is a registered trademark of Techno Electromech and Techno USA LLC. Specifications and Dimensions subject to change without notice. Atlanta | San Antonio | Los Angeles

# Packing

ltem	Qty/CTN	Carton Size	Gross Weight	20GP	40GP	40HQ
60W		600 X 375 X150mm 23.62" X 14.76" X5.90"	6.9KG - SF 7.1KG - DI 6.8KG - TR	823pcs	1588pcs	2000pcs
100W	1PCS		6.9KG - SF 7.1KG - DI 6.8KG - TR			
120W			6.82KG - SF 7.12KG - DI 6.7KG - TR			
150W			6.82KG - SF 7.12KG - DI 6.7KG - TR			
200W	200W 240W 300W	790 X 375 X150mm 31.10" X 14.76" X5.90"	9.75KG - SF 9.97KG - DI 9.53KG - TR	636pcs	1227pcs	1545pcs
240W			9.75KG - SF 9.97KG - DI			
300W			9.53KG - TR 10.3KG - SF 10.6KG - DI			
			10.15KG - TR			

TekTron (Techno USA LLC) dba Techno LED Lights. 2763 Meadow Church Road, Suite 140, Duluth, GA-30097. Phone: 678-456-4810 | Fax: 678-456-4810 | Toll Free: 1 844-552-8272 sales@technoledlights.com | www.technoledlights.com



© 2020 Techno USA LLC. All rights reserved. Techno LED Lights reserves the right to make changes to specifications and/or discontinue any product at anytime without the notice . Information presented in this document is reliable and accurate, It does not represent any quotation or contract. No liability will be accepted by the contributor by the publisher for any consequences for its use. Reproduction in whole or part is prohibited without prior consent of the copyright owner. TK-SAL2\_June-20