# ADAMS LED

Architectural Outdoor




PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	



#### **FEATURES**

- Steel Housing w/ Textured Black Polyester Powder Coat Finish
- Aluminum Heat-Sink Plate
- Solid Top and Bottom End Plates
- . Luminous White Acrylic Panels
- Thermal Compensation Technology Ensures Longer LED Lifetime Ideal For Fixtures Being Placed in Area w/ Fluctuating or Higher Ambient TemPeratures
- Surge Protector
- Mounts Directly to 4" Junction Box (By Others)
- ADA Compliant
- CSA Listed Wet Location
- LED Light Fixture
- Mounting Hardware Included
- Vandal Resistant

### LINE DRAWING



## **FINISHES**





Antique

Silver









Black





Textured White

For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





TERONLIGHTING.COM

# ADAMS LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
<b>AD</b> - Adams	L18.0-TE500 - 18W @ 500mA ELV Dimming Driver L37.0-ZE1100 - 37.0W @ 1100mA 4-Wire 0-10V Dimming Driver	120V 277V (120 - 230V Dimmable)	Not Applicable
ORDER INFO			
AD	L37.0-ZE1100	120V	Not Applicable

Example ^ (may not represent a manufacturable product)

#### Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver SN - Sand SW - Swedish Steel  TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	27K - 2700K Color Temp 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	F - Fused TP - Tamper Resistant Screws WAL - White Acrylic
ORDER INFO			
Not Applicable	AC	27K	F

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
AD	L18.0	80 CRI Typ.     30K - 3000K     Color Temp     2484 LED     Source Lumens     138 LED Source     Lumens Per Watt		
	L37.0	80 CRI Typ.     30K - 3000K     Color Temp     3835 LED     Source Lumens     103.6 LED Source     Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens Panel Set	9800660	Don't see the configuration you are looking for? Call us today at (513) 858-6004

