DUVAL LED

Architectural Outdoor








FEATURES

- Steel Housing w/ Textured Black Polyester Powder Coat Finish
- Aluminum Heat-Sink Plate
- Solid Top and Bottom End Plates
- . Luminous White Acrylic Panels
- Thermal Compensation Technology Ensures Longer LED Lifetime, Which is Ideal For Fixtures Being Placed in Area w/ Fluctuating or Higher Ambient Temperatures
- Surge Protector
- Mounts Directly to 4" Junction Box (By Others)
- CSA Listed Wet Location
- LED Light Fixture
- · Mounting Hardware Included
- Vandal Resistant

LINE DRAWING

LINE DRAWING NOT TO SCAL



FINISHES







Lighting Inc.

DUVAL LED

Architectural Outdoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core

PRODUCT CODE SOURCE/WATTAGE		VOLTAGE	DIMMING DRIVER	
DV - Duval	L37.0-ZE1100 - 37.0W @ 1100mA 0-10V Dimming Driver	120 - 270V	Not Applicable	
ORDER INFO				

Example ^ (may not represent a manufacturable product)

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver MB - Metallic Black SN - Sand SW - Swedish Steel TB - Textured Black (Standard) BZ - Textured Bronze TW - Textured White	27K - 2700K Color Temp 30K - 3000K Color Temp 35K - 3500K Color Temp 40K - 4000K Color Temp 51K - 5100K Color Temp	EB - 5.1W Integral Emergency Battery F - Fused TP - Tamper-Proof Screws
ORDER INFO			
Not Applicable	AC	27K	EB

Example ^ (may not represent a manufacturable product)

PROD	SOURCE	30K SPECS		
PROD DV	L37.0	30K SPECS • 30K - 3000K Color Temp • 3835 LED Source Lumens • 87.2 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens Panel Set	9800660	Don't see the configuration you are looking for? Call us today at (513) 858-6004

