ROYAL EB LED

Architectural Outdoor






PROJECT: TYPE: PO#: COMMENTS:

QTY:

FEATURES

- Steel Fascia w/ Textured Black Polyester Powder Coat Finish
- Luminous White 75% DR Acrylic Diffuser
- Steel Mounting Pan w/ Hi-Reflectance White Powder Coat Finish
- Aluminum Reflector
- Mounts Directly to 4" Junction Box (By Others)
- Constant Current
- Dimmable to 10% From 120V to 230V
- CSA Listed Wet Location
- Emergency Battery Available
 - LED Light Fixture
 - Mounting Hardware Included

LINE DRAWING







TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 1







ROYAL EB LED

Ð

Architectural Outdoor		PO#: COMMENTS:	QTY:
SF 📋 💷 🍹		COMMENTS.	
Fixture Core			
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
RLB - Royal EB	L20.0-ZE700 - 20.0W @ 700mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	120V 277V	Not Applicable

PROJECT: TYPE:

ORDER INFO	L25.0-ZE875 - 25.0W @ 875mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V) L35.0-ZE1150 - 35.0W @ 1150mA Line Voltage 4-Wire Dimming Driver (Dimmable 0 - 10V)	(50 / 60Hz)	
RLB	L20.0-ZE700	120V	Not Applicable
Example ^ (may not represent a man	ufacturable product)		
Aesthetics & Options			

TRIM		FINISH	COLOR TEMP	OPTIONS
Not Applicable		AC - Antique CopperTB - Textured Black (Standard)AS - Antique SilverBlack (Standard)BT - Bronze MistBZ - Textured 	40K - 4000K Color Temp	F - Fused TP - Tamper Resistant Screws EB - Integral Emergency Battery (Please Specify Voltage)
ORDER INFO				
Not Applical	ble	AC	27К	F
		manufacturable product)	· · · · ·	
PROD	SOURCE	30K SPECS		
RLB	L20.0 L25.0	 30K - 3000K Color Temp 2309 LED Source Lumens 115.5 LED Source Lumans Per Watt 30K - 3000K Color Temp 2887 LED Source Lumens 115.5 LED Source 		
	L35.0	Lumens Per Watt • 30K - 3000K Color Temp • 3926 LED Source Lumens • 112.2 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White 75% DR Acrylic Lens	3051160	Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM



We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2