



## **APPLICATION**

The UCL series is a next generation, direct wire undercabinet fixture that Provides task or accent lighting in commercial, retail, hospitality and residential applications. Ideal for use under and over cabinets, display cases, task lighting, office lighting, coves and utility/work areas. Standard knockouts are located on top, back or ends for direct connection. A direct wire UL listed connector is included and is suitable for 3/8" flexible conduit or 3 wire Romex.

#### **FEATURES**

- High-transmission (White) Acrylic lens with excellent distribution and uniformity.
- · Direct replacement for fluorescent
- 120V line voltage fixture
- Low profile (1" deep)
- Hard-wire connections
- Four finishes available (white, black, nickel and oil-rubbed bronze)
- Optional Rocker switch
- Hinged Wireway cover
- Option for 3000/4000 Kelvin, Duel Kelvin switching

# **QUICK SHIP**

UCL-9-5-120D-930/40-WH UCL-12-5-120D-930/40-WH UCL-18-9-120D-930/40-WH UCL-21-9-120D-930/40-WH UCL-24-9-120D-930/40-WH UCL-33-14-120D-930/40-WH UCL-42-18-120D-930/40-WH

## HOUSING

Low profile steel housing available in white, nickel, satin, or oil rubbed bronze finishes. Designed to prevent "hot spots" on counter tops.

#### **MOUNTING**

Designed for mounting on 4" electrical

#### **ELECTRICAL**

Equipped standard with 120V 15-100% triac dimming driver.

### LISTING

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards.

## WARRANTY

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

## ORDERING INFORMATION

Example Model Number: UCL-12-4-120D-930-WH UCL DRIVER TYPE COLOR TEMPERATURE **FINISH SERIES** LENGTH WATTAGE 5-5W, 9" Length<sup>2</sup> 5-5W, 12" Length<sup>2</sup> 9-9W, "18" Length<sup>2</sup> 9-9W, "21" Length<sup>2</sup> 9-9W, 24" Length<sup>2</sup> 14-14W, 33" Length<sup>2</sup> 9-9" Length 12- 12" Length<sup>2</sup> 18- 18" Length<sup>2</sup> 24- 24" Length<sup>2</sup> 33- 33" Length<sup>2</sup> 42- 42" Length<sup>2</sup> 120D- 120V, Triac Dimming<sup>2</sup> 930/40-90 CRI; 3000-4000 Kelvin NS- Nickel Satin<sup>12</sup> ORB- Oil Rubbed Bronze<sup>1 2</sup> MV- 120-277V1 Dual color switch **930**-90 CRI; 3000 Kelvin<sup>1</sup> **940**-90 CRI; 4000 Kelvin<sup>1</sup> WH- White2 **18**-18W, 42" Length<sup>2</sup>

Notes:

 $^{\rm 1}\!\text{Made}$  to order items. Minimum 90 day lead time. Minimum 500 order quantity.

<sup>2</sup>Energy star listed