

UHX SERIES INDUSTRIAL LIGHTING

UHXE-165-220W-MCTP4-SR-WH
POWER AND CCT- ADJUSTABLE UFO HIGHBAY


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



12 1/7" (W) X 2 1/2" (H)

In a aluminium shell designed for heat dissipation, UHXE is IP65 water resistant rated and ideal for general site lighting, alleys, loading docks, doorways, pathways, parking areas, warehouses and storage buildings.

Features

- Waterproof design, suitable for wet locations
- Aluminum Heat Sink, Outdoor Powder Coating Finish
- Optical Lens: PC Materials High Light Transmittance, Anti-UV, Fire-Resistant
- Multi Color Temperature & Multi Power (Selectable Switch Located On The Driver Housing)

Technical Specifications

Electrical:

- Input Wattage: 165W/190W/220W
- Input Voltage: 120-277V 50/60Hz
- Power Factor: >0.9
- THD: <20%
- Efficacy: 140 LPW

Mechanical:

- Aluminum Heat Sink, Outdoor Powder Coating Finish
- Nano Coating Heat Dissipation Technology
- Optical Lens: PC Materials High Light Transmittance, Anti-UV, Fire-Resistant
- Twist-Lock Zhaga Socket Pre-Installed. See Motion Sensor Accessories.
- 3.3' SJTW 18,3 AWG Power Cable
- 3.3' SJTW Dimming Cable
- LED PCB Board: High Conductive, Waterproof, Aging Resistance, salt mist Resistance, Ensure the Safety and Long Lifespan
- Operating temperature: -40°F to 122°F
- IP rating: IP65, Wet Locations
- 5-Year Warranty

Lighting:

- Dimming: 0~10V
- Total Lumens: 30800LM
- Multi Color Temperature & Multi Power (Selectable Switch Located On The Driver Housing)
- Color Temperatures: 3000K/3500K/4000K/5000K
- Color Rendering index: > 80
- Beam Angle: 90°
- Lifespan: 50,000 Hrs

Applications:

- Ideal for general site lighting, alleys, loading docks, doorway, pathway, parking areas, warehouses and storage buildings.

Other Models:

- 220W | 30800LM | UHXE-165-220W-MCTP4-SR




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |




WG-02092022

Photometrics: UHXE-165-220W-MCTP4-SR-WH



BUG Rating: B4-U3-G1



Area 65'x 65' Mounting Height: 9'

Performance Table: UHXE-165-220W-MCTP4-SR-WH

MODEL NO.	Wattage	Voltage	Lumens	Color Temp	BUG Rating	LPW
UHXE-165-220W-MCTP4-SR-WH	165W	120-277V	23100LM	3000K	B4-U3-G1	140
	190W		26600LM	3500K		
	220W		30800LM	4000K 5000K		

Sample Ordering

Model Wattage Wattage Color Temp. Sensor Ready Housing

UHXE - 165 - 220W - MCTP4 - SR - WH

Accessories:

- Blank = No Accessory
- HB-RING = HIGHBAY TOP RING ADAPTER, 1/2in
- HB-EB-50/75 = HIGHBAY EXPANSION BUSHING FROM 1/2in TO 3/4"
- UHX-SMB = UHX SERIES SURFACE MOUNTING YOKE BRACKET
- UHX-SC = UHX SERIES 22" SAFETY CABLE
- UHXE-PCR-B-90D = UHXE 165-220W 90-DEGREE PC REFLECTOR
- UHXE-PCR-B-60D = UHXE 165-220W 60-DEGREE PC REFLECTOR
- UHXE-RPMB = UHXE 3.3 FT. RIGID PIPE STAND WITH TOP CANOPY
- UHX-SA-5075 = 1/2 IN STEM-MOUNTING ADAPTER WITH CABLE PASSAGE WITH 1/2 IN TOP THREAD
- WEC-3PR-72-TLB-WH = 600W Max, ZHAGA 12-24VDC PIR SENSOR, WHITE, WITH BASE (OPTIONAL REMOTE CONTROL WEC-3RC)

Factory-Installed Option:

- Blank = No Accessory
- OPT-EM-UHX = EXTERNAL EMERGENCY BACKUP BATTERY INSTALLED ON TOP OF THE FIXTURE
- OPT-HBC=125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V, 16/3TL, WHITE
- OPT-HBC=277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V, 16/3TL, WHITE
- OPT-HBC=125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A, 125V, 18/3TL, WHITE
- OPT-SEN-UHX = MICROWAVE BI-LEVEL SENSOR

Example:

1. UHXE-165-220W-MCTP4-SR-WH (FOR UHXE 220W MCTP FIXTURE 120-277V)
2. UHXE-165-220W-MCTP4-SR-WH (FOR UHXE 220W MCTP FIXTURE 120-277V)
HB-RING (HIGHBAY TOP RING ADAPTER, 1/2in)



ACCESSORIES:



HB-RING
HIGHBAY TOP RING
ADAPTER, 1/2in



HB-EB-50/75
HIGHBAY
EXPANSION
BUSHING FROM 1/2in
TO 3/4"



UHX-SMB
UHX SERIES SURFACE
MOUNTING YOKE
BRACKET



UHX-SC
UHX SERIES 22"
SAFETY CABLE



UHX-SA-5075
1/2 IN STEM-MOUNTING
ADAPTER WITH CABLE
PASSAGE WITH 1/2 IN TOP
THREAD



UHXE-RPMB
UHXE 3.3 FT. RIGID PIPE
STAND WITH TOP CANOPY



UHXE-PCR-B-90D
UHXE-80-150W 90-DEGREE
PC REFLECTOR



UHXE-PCR-B-60D
UHXE-80-150W 60-DEGREE
PC REFLECTOR



WEC-3PR-72-TLB-WH
600W Max, ZHAGA 12-24VDC
PIR SENSOR, WHITE, WITH
BASE (OPTIONAL REMOTE
CONTROL WEC-3RC)

FACTORY-INSTALLED OPTION:



OPT-HBC-125SB-WH
STRAIGHT BLADE PLUG 10FT, 15A,
125V, 18/3TL, WHT



OPT-HBC-125TL-WH
NEMA TWIST-LOCK PLUG 8FT, 15A,
125V, 16/3TL, WHT



OPT-HBC-277TL-WH
NEMA TWIST-LOCK PLUG 8FT, 15A,
277V, 16/3TL, WHT



OPT-EM-UHX
EXTERNAL EMERGENCY
BACKUP BATTERY INSTALLED
ON TOP OF THE FIXTURE
(The bracket can be painted)

