UFO LED High Bay Light





Characteristics

- It's made of Cree SMD3030 and LiFud / Sosen led driver for application which requires maximum performance and minimum maintenance.
- The die-cast aluminum housing, sealed and gasket optics compartment combine to make LED light virtually impenetrable to contaminants
- This high bay light fixture can get the same lumen intensity as triple HPS / HPS / HID / Metal halide lamp for warehouse, parking lot and plant lighting and other lighting applications.


CONSTRUCTION & MATERIALS


- Heavy duty die-cast aluminum housing, fully sealed to be dirt and bug proof
- ▶ High quality polycarbonate lens with 60 / 90 / 120 degree beam angle
- New model design is easy for installation and maintenance.
- IP 65 waterproof protection
- Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- ▲ LiFud / Sosen led driver
- Qualified Cree SMD3030 LED source


| Power | 100W | 150W | 200W | 240W | |
|--------------------------|------------------------------|--------------|--------------|--------------|--|
| Certification | ETL / cETL | | | | |
| Lumen | 15000lm±5% | 22500lm±5% | 30000lm±5% | 36000lm±5% | |
| Luminous Efficiency | 150lm/w±5% | | | | |
| Input Voltage | 120-277V / 347-480V, 50-60Hz | | | | |
| LED Brand | CREE | | | | |
| Power Supply | LiFud / Sosen | | | | |
| сст | 3000-6500K | | | | |
| CRI | >75Ra | | | | |
| Sensor | Yes (optional) | | | | |
| Beam Angle | 60°/90°/120° | | | | |
| Ingress protection | Ip65 | | | | |
| Operation Temperature | (-30~60°C) | | | | |
| Lamp Dimension | Ф250x182.5mm | Ф280x184.5mm | Ф320x189.5mm | Ф350x189.5mm | |
| Net Weight | 2.2KG | 3.4KG | 4.4KG | 5.4KG | |


Installation

- 1. Hook Suspended Mounting
- 2. Surface Mounting
- 3. Conduit Suspended Mounting












Light Distribution



60 degree





-/+180


150

120

-150

-120

120 Degree



| NO | Power | Carton Size (LxWxH) | G.W./Ctn | QTY/Ctn (PCS) |
|----|-------|------------------------|-----------|------------------|
| 1 | 100W | 12.2x12.2 x8.2 inches | 6.40 lbs | 1 |
| 2 | 150W | 13.4x13.4 x 8.2 inches | 8.80 lbs | 1 |
| 3 | 200W | 15.3x15.3 x 8.2 inches | 10.80 lbs | 1 |
| 4 | 240W | 16.1x 16.1x 8.2 inches | 12.80 lbs | 1 |

