



## Vapor Tight Slim Tandem, Multi-Volt

### Specifications

- Enclosed and gasketed housing will withstand most critical environments.
  - Weather and chemical resistant, corrosion free, and impervious to vapors, dust, moisture, and for wet locations.
  - Available in lengths of 4' or 8' (nominal)
  - Surface, stem or chain mountable
- Applications Food handling and processing facilities, refrigerated storage, drug and chemical plants. Use in shower areas, parking garages, pedestrian and roadway tunnels, and outdoor public areas.
- Additional Features • With Plug



### General Characteristics

**Material**

**Cover**

**Bulb**

**Finish**

**Safety Rating**

Plastic

Clear

T8

White

ETL Listed

### Fixture Characteristics

**Collection**

**Shape**

**Number of Lights**

**Bulb Max Wattage**

**Mounting**

**Use Location**

Plug & Play

Linear

4 - Light

32 Max

Surface

Indoor

### Electrical Characteristics

**Watts**

**Volts**

4x 32

Multi-Volt

### Product Dimensions

**Item Dimensions (in)**

(W) 6.80 (H) 4.35 (D) 99.70

### Product Data

**Item Number**

**Case Quantity**

**Barcode on SKU**

**Brand**

**Description**

92684-SU

1

653703926841

SUNLITE

VTST-4-F32T8-MV