



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

This very tough enclosure is ideal for demanding environments that require a smaller LED enclosure. For use in both indoor and outdoor applications where dust and water resistance is required. Ideal for refrigerated storage, food processing facilities, beverage and bottling facilities, exterior retail, construction sites and gymnasiums.

FEATURES & BENEFITS

- Compact size
- Poured in place gasket and latches seal the enclosure from hostile environments
- Very tough diffusers resist breakage and reduce replacement costs
- Optional cable, V-hook or ceiling mount accessories
- Very durable
- Easy to clean and service



DIMENSIONS

26.6”L x 14.5”W x 5.8”H

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: VWHBS LED 100 DMV 50

VWHBS LED

1. SERIES	2. GEAR	3. WATTAGE/LUMENS ¹	4. DRIVER ²	5. LENS	6. COLOR TEMP	7. EM
VWHBS	LED	80 80W 8000 Lumens	DMV 120-277V Multivolt 0-10V Dimmable	Blank Clear Acrylic FR Frosted Acrylic PC Clear Polycarbonate PF Frosted Polycarbonate	30 3000K 35 3500K 40 4000K 50 5000K	EM Emergency Battery Pack 10W ~ 1700 lumens EM5 Emergency Battery Pack 5W ~ 850 Lumens
		100 100W 10000 Lumens				
		140 140W 14000 Lumens				
			SDMV Step dimming Multivolt			
			DHV 347-480VAC 0-10V Dimming			
			D347V 347VAC 0-10V Dimming			
			TDMV Triac Dimming 120-277VAC			
			D120 Triac Dimming 120VAC			
			D277 Triac Dimming 277VAC			

Notes:

¹Consult for custom wattage and lumen packages

²Consult for other driver options (Step dimming, Triac dimming)

8. SENSOR	9. CORD	10. PHOTOCELL
OS Occupancy Sensor	CS Cordset 6' 3 wire	PC120 Photocell 120V
OSW Occupancy Sensor - Wet Location	CS12 Cordset 12' 3 wire	PC277 Photocell 277V
OSC Occupancy Sensor Cold Temperature		
OSD Occupancy Sensor - 0-10V Dimmable		
SS Occupancy Sensor - Internal Microwave		

*Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip CS - Cord-set	(Blank) 3 Wire 4 - 4 Wire 5 - 5 Wire 6 - 6 Wire	(Blank) 6 feet 8 - 8 feet 10 - 10 feet 12 - 12 feet 15 - 15 feet	(Blank) No Plug P* - Standard Plug TL* - Twist Lock	BK - Black WH - White	(Blank) 120-277V 120 - 120V 277 - 277V 347 - 347V 480 - 480V	15 - 15 Amps 20 - 20 Amps

ACCESSORIES

- H137 V-Hook
- VWFHB-MBCM Flexible Ceiling Mount



Surface mount fixture 1.25" from ceiling (VWFHB-MBCM)



V hook (H137) sold individually (need 2 per fixture)

REPLACEMENT PARTS

- H203 Stainless Mounting Strap
- H199 Zinc Plated Mounting Strap



Accessory available for 3/4" hub for single point mounting



Stainless hardware for mounting straps and latches

Dimensions and specifications subject to change without notice.

