

W108D

Wall Sconce



Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity
 LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD
JA8 Type: High Power Factor (> 0.98), Low THD (< 10%)
LED Driver, 120V Triac Dimming Type (Min. Dimming Level 3%)
Flicker Free: Meets JA10 Standard

Lamp


Integrate LED Module, 3000K LED
 More Color Temperature Option 3500K, 4000K, 5000K
JA8 Type: 3000K only, LM80/TM21 60,000hrs Min. Rating

Certification

ETL/cETL Listed
JA8 Type – CEC Listed, Meets Title24 JA8 Requirements

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	Lamp	LED CT	Lumen (TYP)	Finish/Shade	Dimension (W x H x D)	Energy Star
W108D-62-xxxxK	120V	12W	Strip	3000K / >80	1000	Satin Nickel / Acrylic	5.1" x 14.5" x 4.0"	Yes
W108D-30-xxxxK	120V	12W	Strip	3000K / >80	1000	ORB / Acrylic	5.1" x 14.5" x 4.0"	Yes
W108D-MCT	120V-277V	12W	Strip	3000K / >80	1000	Satin Nickel/ Acrylic	5.1" x 14.5" x 4.0"	Yes

JA8 Type

Model	Input Voltage	Input Wattage	LED CT/CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H x D)	CEC T24 Listed
W108D(JA8)	120V	12W	3000K / >90	850	Satin Nickel/ Acrylic	5.1" x 14.5" x 4.0"	Yes